

PI.068 - QUICK NOTES: Product Coverage Chart

Revised: 4.11.10

The charts below should be used as for guideline purposes only to help determine the approximate coverages of the more popular Elite Crete Systems products. Coverages will vary depending on surface texture, application technique, application tools and specific finishes installed.

THIN-FINISH™ Overlay (Just add water):

Application	Volume	Coverage
THIN-FINISH™ Overlay - Skim, Base or Broom Coat	1 bag	250 to 300 sq. ft.
THIN-FINISH™ Overlay - Splatter Texture, Knockdown or Slate Trowel	1 bag	150 to 175 sq. ft.
THIN-FINISH™ Countertop – As “gel” coat for GFRC countertops	1 bag	150 to 200 sq. ft.
THIN-FINISH™ Vertical – As “venetian stucco” finish when mixed with MICRO-FINISH™	1 bag (added to one bag of MICRO-FINISH™)	225 to 300 sq. ft.

TEXTURE-PAVE™ Overlay (Just add water):

Application	Volume	Coverage
TEXTURE-PAVE™ Overlay – ¼” Thin Stamped Overlay	3 bags	75 sq. ft.
TEXTURE-PAVE™ Countertop – As “pack” coat for GFRC countertops	3 bags (at ½” thick)	38 to 40 sq. ft.

MICRO-FINISH™ Overlay (Just add water):

Application	Volume	Coverage
MICRO-FINISH™ Overlay – Very Smooth “Steel Trowel Like” Finish	1 bag	200 to 300 sq. ft.
MICRO-FINISH™ Vertical – As “venetian stucco” finish when mixed with THIN-FINISH™	1 bag (added to one bag of THIN-FINISH™)	225 to 300 sq. ft.

CSS EMULSION™ – Solventborne Clear Sealer (must be diluted prior to use):

Application Being Applied To	Volume	Coverage
Smooth Finish Coat	1 gallon (diluted 1:1)	@ 350 sq. ft.
Slate Trowel Down or Splatter Texture or Knockdown Finish	1 gallon (diluted 1:1)	@ 200 sq. ft.
Thin Stamped Overlay	1 gallon (diluted 1:1)	@ 260 sq. ft.
Conventional Stamped Concrete	1 gallon (diluted 1:1)	@ 260 sq. ft.

CSS-V EMULSION™ – Solventborne Clear Sealer – VOC Compliant (must be diluted prior to use):

Application Being Applied To	Volume	Coverage
Smooth Finish Coat	1 gallon (diluted 1:1)	@ 350 sq. ft.
Slate Trowel Down or Splatter Texture or Knockdown Finish	1 gallon (diluted 1:1)	@ 200 sq. ft.
Thin Stamped Overlay	1 gallon (diluted 1:1)	@ 260 sq. ft.
Conventional Stamped Concrete	1 gallon (diluted 1:1)	@ 260 sq. ft.

WCS EMULSION™ – Waterborne Concrete Sealer:

Application Being Applied To	Volume	Coverage
Smooth Finish Coat	1 gallon	@ 350 sq. ft.
Slate Trowel Down or Splatter Texture/Knockdown Finish	1 gallon	@ 250 sq. ft.
Thin Stamped Overlay	1 gallon	@ 300 sq. ft.
Conventional Stamped Concrete	1 gallon	@ 300 sq. ft.

ULTRA-STONE™ Antiquing Stain – Non-Acid Based Translucent Stain:

Application Being Applied To	Volume	Coverage
Slate Trowel Down or Splatter Texture/Knockdown Finish	1 gallon (diluted 3:1)	@ 150 sq. ft.
Thin Stamped Overlay – Texture Skin Finish	1 gallon (diluted 3:1)	@ 150 sq. ft.
Thin Stamped Overlay – Stamp w/ Grout Lines	1 gallon (diluted 3:1)	@ 100 sq. ft.

CHEM-STONE™ Reactive Stain – Acid Based Reactive Chemical Stain:

Application Being Applied To	Volume	Coverage
Smooth Finish Coat	1 gallon	@ 250 sq. ft.
Slate Trowel Down or Splatter Texture/Knockdown Finish	1 gallon (diluted 1:1)	@ 200 sq. ft.
Thin Stamped Overlay – Texture Skin Finish	1 gallon (diluted 1:1)	@ 175 sq. ft.
Thin Stamped Overlay – Stamp w/ Grout Lines	1 gallon (diluted 1:1)	@ 125 sq. ft.
Conventional Stamped Concrete	1 gallon (diluted 1:1)	@ 125 sq. ft.

HYDRA-STONE™ Dye Stain:

Application Being Applied To	Volume	Coverage
Smooth Finish Coat	1 gallon (Reduced 1:1)	@ 225 sq. ft.
Slate Trowel Down or Splatter Texture/Knockdown Finish	1 gallon (Reduced 1:1)	@ 200 sq. ft.
Thin Stamped Overlay – Texture Skin Finish	1 gallon (Reduced 3:1)	@ 150 sq. ft.
Thin Stamped Overlay – Stamp w/ Grout Lines	1 gallon (Reduced 3:1)	@ 100 sq. ft.

CLEAN-PRINT™ Liquid Release Agent:

Application	Volume	Coverage
Thin Stamped Overlay	1 gallon	@ 150 to 175 sq. ft.

E100-PT1™ Crystal Clear and E100-PT4™ Pigmented Epoxy:

Application Being Applied To	Volume	Coverage
Smooth Conventional concrete or overlayment	1 gallon	@ 150 sq. ft.
REFLECTOR™ Enhancer Flooring Systems (E100-PT1™ Crystal Clear)	1 gallon	@ 70 to 90 sq. ft.
Slate Trowel Down or Splatter Texture/Knockdown Finish	1 gallon	@ 100 sq. ft.
Thin Stamped Overlay	1 gallon	@ 100 sq. ft.

E100-PT3™ Clear Waterborne Epoxy:

Application Being Applied To	Volume	Coverage
Smooth Conventional concrete or overlayment	1 gallon	@ 250 to 300 sq. ft.
Slate Trowel Down or Splatter Texture/Knockdown Finish	1 gallon	@ 175 to 250 sq. ft.
Thin Stamped Overlay	1 gallon	@ 200 to 250 sq. ft.

PROTEC-ALL™ Polyurethane Finish:

Application Being Applied To	Volume	Coverage
Smooth Conventional concrete or overlayment with epoxy applied	1 gallon	@ 400 to 500 sq. ft.
Slate Trowel Down or Splatter Texture/Knockdown Finish with epoxy applied	1 gallon	@ 350 to 450 sq. ft.
Thin Stamped Overlay with epoxy applied	1 gallon	@ 375 to 475 sq. ft.

E100-VB5™ Waterborne Epoxy Vapor Barrier:

Application Being Applied To	Volume	Coverage
Smooth Conventional concrete	1 gallon	@ 250 to 300 sq. ft.