

SDS.101 – Safe Product Usage – MUST READ

Revised: 3.14.15

To ensure the safe use of our products and to comply with OSHA Hazard Communication Standards, Elite Crete Systems, Inc. provides Safety Data Sheets for the various products for your safety. It is critical that you read and fully understand the precautions associated with each product before use and practice safe product usage to ensure the safety of you and others.

Below is a brief description of the precautions that should be taken into consideration before and during use of some of the more hazardous products. It is still however recommended that you read the full Safety Data Sheet for each and every product to fully understand the precautions.

PRODUCT	PRECAUTIONS
Pre-Mixed Overlays: - TEXTURE-PAVE™ - THIN-FINISH™ - MICRO-FINISH™	Do not breathe dust. Contains cement and silica quartz. Use dust mask while mixing. Protect your skin as cement can cause burn. Silica quartz can cause permanent lung damage and silicosis.
CSS EMULSION™	HIGHLY FLAMMABLE. Use only with adequate air ventilation to ensure air movement of solvent fumes away from the application. Extinguish any and all sources of flame or spark. Contains solvent and additional solvent is required for reduction. Do not breathe solvent vapors. Use approved air mask. Protect your eyes.
CHEM-STONE™	Corrosive. Protect your skin and eyes. Contains hydrochloric acid. Do not breathe acid vapors.
HYDRA-STONE™ (Dye Stain and Reducer)	HIGHLY FLAMMABLE. Use only with adequate air ventilation to ensure air movement of solvent fumes away from the application. Extinguish any and all sources of flame or spark. Contains solvent and additional solvent is required for reduction. Do not breathe solvent vapors. Use approved air mask. Protect your eyes.
CLEAN-PRINT™	Combustible. Use only with adequate air ventilation to ensure air movement of solvent fumes away from the application. Extinguish any and all sources of flame or spark. Contains solvent and additional solvent is required for reduction. Do not breathe solvent vapors. Use approved air mask. Protect your eyes.
E100 Series™ Epoxy (PT1, PT4, PT3, VB5, NV4, NV5, UV1, FS4, UL7 and VR1)	Part B is mildly corrosive. Protect your skin and eyes.
SPARTIC-ALL™ RM	FLAMMABLE. Use only with adequate air ventilation to ensure air movement of solvent fumes away from the application. Extinguish any and all sources of flame or spark. Contains solvent. Do not breathe solvent vapors. Use approved air mask. Protect your eyes.
AUS-50™ & AUS-HD™	HIGHLY FLAMMABLE. Use only with adequate air ventilation to ensure air movement of solvent fumes away from the application. Extinguish any and all sources of flame or spark. Contains solvent. Do not breathe solvent vapors. Use approved air mask. Protect your eyes.
AUS-V™	Part B is mildly corrosive. Protect your skin and eyes.
EXIT™	Contains light non-flammable alcohol. Protect your skin and eyes.

This document is intended to provide a warning for the safe use of Elite Crete Systems, Inc. products but does not replace the information contained in the Safety Data Sheets or the Technical Data Sheets for the products. Our intention is to help provide the safest use of our products as possible.

It is recommended that you share and review this document as well as the associated Safety Data Sheets with all of your employees as well as keep copies of such documents on the job site and work vehicles at all times.

If you require additional information or assistance, please feel free to call us at 888-323-4445 or 219-465-7671 and we will be of assistance.

Think safety and work safely at all times.