

1061 Transport Drive, Valparaiso, IN 46383 Toll Free 888.323.4445 • P 219.465.7671 F 219.531.0898 • www.elitecrete.com

TD.444 - TECHNICAL DATA: WCS EMULSION™

Revised: 1.20.16

Product Name: WCS EMULSION™ – Waterborne Clear Sealer

Trade Name: WCS EMULSION™

Product Class: Acrylic Co-polymer Sealer

Description: A blended copolymer resin blended as a clear sealer

Use Applications:

Provides a light protection for sealing and protecting concrete surfaces.

Vertical concrete applications.

Key Features:

Increased levels of water, chemical, UV and abrasion resistance.

Increase versatility and application range.

Product Properties:

- Appearance White clear liquid
- Smell Faint ester
- Volatile Organic Content 89 g/l
- GT Temperature +19 degree Celsius
- Viscosity @ 25 degrees Celsius @ 20 rpm 250 to 300
- pH 7.5 ± 1
- Flammability N/A
- Density, Lb. per gal. 8.7 to 9
- Weight, Lb. per gal. 8.8 to 8.9
- Application temperature 40° 110° F
- Cured 12-24 hours
- Resistance to moisture deterioration Excellent
- Resistance to weather, including UV and freeze/thaw cycles Excellent

Available Packaging:

- Stock 1 gallon pails, 5 gallon pails, 36 pails per pallet or 55 gallon drums
- Special Order Inquire

Suggested Storage:

- Do not allow to freeze
- Shelf Life 6 months to a year