

Safety Data Sheet

According to OSHA Hazard Communication 29 CFR Part 1910.1200

Version: 1.0

Revision: 3/15/21

Trade Name: AUS-50™ – ALIPHATIC URETHANE SEALER

SECTION 1 Identification

Product Type:: MOISTURE CURE
URETHANE
Product Name: AUS-50™
Supplied by: Elite Crete Systems
1151 Transport Drive,
Valparaiso, IN 46383
Toll Free: 888.323.4445
Tel: (219) 465-7671
www.elitecrete.com

For Emergency Medical Assistance:

Call Health & Safety Information Services

(1-866-303-6949)

For Emergency transportation Information:

CHEMTREC US DOMESTIC: 1-800-424-9300

CHEMTREC INTERNATIONAL: 1-703-527-3887

SECTION 2 Hazard(s) identification

*** **EMERGENCY OVERVIEW** ***: Flammable liquid and vapor. May be fatal if swallowed. Suspect cancer hazard.

GHS Classification

Acute Tox. 4, Asp. Tox. 1, Carc. 2, Eye Irrit. 2, Flam. Liq. 3, STOT RE 2, STOT SE 3 RTI, Skin Irrit. 2

Canadian WHMIS Classification:


D2B - Toxic material causing other toxic effects.
(Pictograms)



TGD Canada



NFPA ratings (scale 0 - 4)



Health = 3
Fire = 3
Reactivity = 0

HMIS-ratings (scale 0 - 4)

Health	3
Fire	3
Reactivity	0

Health = 3
Fire = 3
Reactivity = 0
Personal Protection = X

Symbol(s) of Product



Signal Word Danger

Safety Data Sheet

According to OSHA Hazard Communication 29 CFR Part 1910.1200

Version: 1.0

Revision: 3/15/21

Trade Name: AUS-50™ – ALIPHATIC URETHANE SEALER
--

GHS HAZARD STATEMENTS

Flammable Liquid, category 3

Aspiration Hazard, category 1

Skin Irritation, category 2

Eye Irritation, category 2

Acute Toxicity, Inhalation, category 4

STOT, single exposure, category 3, RTI

Carcinogenicity, category 2

STOT, repeated exposure, category 2

H226 Flammable liquid and vapor.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

GHS PRECAUTIONARY STATEMENTS

P201

Obtain special instructions before use.

P202

Do not handle until all safety precautions have been read and understood.

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P240

Ground/bond container and receiving equipment.

P241

Use explosion-proof electrical/ventilating/lighting/equipment.

P242

Use only non-sparking tools.

P243

Take precautionary measures against static discharge.

P260

Do not breathe dust/fume/gas/mist/vapors/spray.

P264

Wash thoroughly after handling.

P271

Use only outdoors or in a well-ventilated area.

P280

Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310

IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician

P302+P352

IF ON SKIN: Wash with plenty of water

P303+P361+P353

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313

IF exposed or concerned: Get medical advice/attention.

P312

Call a POISON CENTER/doctor/physician if you feel unwell.

P314

Get medical advice/attention if you feel unwell.

P321

Specific treatment (see first aid section on this label).

P331

Do NOT induce vomiting.

P332+P313

If skin irritation occurs: Get medical advice/attention.

P337+P313

If eye irritation persists: Get medical advice/attention.

P362+P364

Take off contaminated clothing and wash it before reuse.

P370+P378

In case of fire: Use appropriate method to extinguish.

P403+P233

Store in a well-ventilated place. Keep container tightly closed.

P403+P235

Store in a well-ventilated place. Keep cool.

P405

Store locked up.

P501

Dispose of contents/container in accordance with local/regional/national/international regulations.

Safety Data Sheet

According to OSHA Hazard Communication 29 CFR Part 1910.1200

Version: 1.0

Revision: 3/15/21

Trade Name: AUS-50™ – ALIPHATIC URETHANE SEALER

SECTION 3 Composition/information on ingredients

<u>Chemical Name</u>	<u>CAS-No.</u>	<u>WT. %</u>	<u>GHS Symbols</u>	<u>GHS Statements</u>
Xylene	1330-20-7	49%	GHS02-GHS07-GHS08	H226-315-319-332-335-351-373
Homo Polymer of HDI	2182-81-2	51%	GHS02-GHS07-GHS08	H225-315-319-332-335-351-373

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

SECTION 4 First aid measures



FIRST AID - EYE CONTACT: Immediately flush eyes with water. Flush eyes with water for a minimum of 15 minutes, occasionally lifting and lowering upper lids. Get medical attention promptly. Remove contact lenses if worn.

FIRST AID - SKIN CONTACT: Remove contaminated clothing. Wash skin with soap and water. Get medical attention. Wash clothing separately and clean shoes before reuse.

FIRST AID - INHALATION: Rescuers should put on appropriate protective gear. Remove from area of exposure. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Keep victim warm. Get immediate medical attention. To prevent aspiration, keep head below knees.

FIRST AID - INGESTION: DO NOT induce vomiting. DO NOT give liquids. Get medical attention immediately.

SECTION 5 Firefighting measures

UNUSUAL FIRE AND EXPLOSION HAZARDS: Flammable liquid and vapor. Vapors/dust may form explosive mixture with air. Vapors can travel to a source of ignition and flash back. Empty containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. Also, do not reuse container without commercial cleaning or reconditioning. Closed container may explode under extreme heat.

SPECIAL FIREFIGHTING PROCEDURES: As in any fire, wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear. Avoid use of solid water streams. Use water with caution. Material will float and may ignite on surface of water. Water may be ineffective in fighting the fire. Water spray to cool containers or protect personnel. Use with caution. Water runoff can cause environmental damage. Dike and collect water used to fight fire.

EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, Foam, Water Fog

SECTION 6 Accidental release measures

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Wear appropriate personal protective equipment. (See Exposure Controls / Personal Protection Section.) Eliminate all ignition sources. Prevent additional discharge of material if able to do so safely. Do not touch or walk through spilled material. Avoid runoff into storm sewers and ditches which lead to waterways. Ventilate spill area. Stay upwind of spill. A vapor suppressing foam may be used to reduce vapors. Collect spilled materials for disposal. Use only non-combustible material for clean-up. Use clean, non-sparking tools to collect absorbed materials. Remove from surface by skimming or with suitable absorbents. Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container.

Safety Data Sheet

According to OSHA Hazard Communication 29 CFR Part 1910.1200

Version: 1.0

Revision: 3/15/21

Trade Name: AUS-50™ – ALIPHATIC URETHANE SEALER

SECTION 7 Handling and storage



HANDLING: Use only in a well ventilated area. Avoid breathing vapor, fumes or mist. Avoid contact with eyes, skin, and clothing. Material accumulates static charge (ignition source). When transferring, follow proper grounding procedures. Use spark-resistant tools. Do not load into compartments adjacent to heated cargo. Use explosion proof equipment. Always open containers slowly to allow any excess pressure to vent. Follow all MSDS/label precautions even after containers are emptied because they may retain product residues.

STORAGE: Keep away from heat, sparks, and flame. Containers can build up pressure if exposed to heat (fire). Store containers in a cool, well ventilated place. Keep container closed when not in use. Protect from direct sunlight. Material is a static accumulator which has the potential of forming ignitable vapor-air mixtures in storage tanks

SECTION 8 Exposure controls/personal protection

Ingredients with Occupational Exposure Limits

<u>Chemical Name</u>	<u>ACGIH TLV-TWA</u>	<u>ACGIH-TLV STEL</u>	<u>OSHA PEL-TWA</u>	<u>OSHA PEL-CEILING</u>
Xylene	100 ppm	150ppm	100 ppm	N.D.

Personal Protection



RESPIRATORY PROTECTION: NIOSH/MSHA approved respirators may be necessary if airborne concentrations are expected to exceed exposure limits.



SKIN PROTECTION: Wear impervious gloves to prevent contact with the skin. Wear protective gear as needed - apron, suit, boots.



EYE PROTECTION: Self- contained breathing apparatus



OTHER PROTECTIVE EQUIPMENT: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.



HYGENIC PRACTICES: Do not eat, drink, or smoke in areas where this material is used. Avoid breathing vapors. Remove contaminated clothing and wash before reuse. Wash thoroughly after handling. Wash hands before eating.

Safety Data Sheet

According to OSHA Hazard Communication 29 CFR Part 1910.1200

Version: 1.0

Revision: 3/15/21

Trade Name: AUS-50™ – ALIPHATIC URETHANE SEALER

SECTION 9 Physical and chemical properties

Appearance:	Clear, transparent liquid	Physical State:	Liquid
Odor:	Aromatic	Odor Threshold:	Isocyanates cannot be smelled until concentrations are above safe exposure limits
Density, g/cm³:	0.872	pH:	Not determined
Freeze Point, °F:	N.D.	Viscosity:	Not determined
Solubility in Water:	Insoluble	Explosive Limits, vol%:	1.0 – 7.0
Boiling Range, °F:	259.7°F (126.5°C)	Flash Point, °F:	75.2°F (24°C)
Evaporation Rate:	N/A	Auto-ignition Temp., °F:	393.8°F (201°C)
Vapor Density:	7 (air=1)weight average 4.42	Vapor Pressure:	7mm Hg

SECTION 10 Stability and reactivity

STABILITY: Product is stable

CONDITIONS TO AVOID: Avoid impact, friction, heat, sparks, flame and source of ignition.

INCOMPATIBILITY: Keep separate from alkalis,. Keep away from acids. Prevent contact with oxidizing materials and alcohols. Absorbs moisture from air. Reacts slowly with water to release CO₂ gas.

HAZARDOUS DECOMPOSITION PRODUCTS: Toxic gases/fumes are given off during burning or thermal decomposition. During combustion carbon monoxide may be formed. During combustion carbon dioxide may be formed.

SECTION 11 Toxicological information



HAZARDOUS POLYMERIZATION: No Information

Information on Toxicological Effects

EFFECTS OF OVEREXPOSURE - INHALATION: Breathing saturated vapors for a few minutes may be fatal. Saturated vapors can be encountered in confined spaces and/or under conditions of poor ventilation. Prolonged inhalation may be harmful. Vapors can cause irritation of the respiratory tract. High concentrations can cause headache, nausea, weakness, lightheadedness, and stupor (CNS depression). May cause dizziness and drowsiness.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: Contact with skin may cause mild irritation. Can be absorbed through skin and produce central nervous system effects. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash). Personnel with pre-existing skin disorders should avoid contact with this product can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

EFFECTS OF OVEREXPOSURE - EYE CONTACT: May cause eye irritation. Symptoms may include stinging, tearing, redness and swelling.

EFFECTS OF OVEREXPOSURE - INGESTION: May be fatal if swallowed. Aspiration hazard if swallowed - can enter lungs and cause damage. Ingestion may cause gastrointestinal tract irritation. May cause nausea and diarrhea.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: Suspect cancer hazard. Possible brain damage from overexposure. The International Agency for Research on Cancer has evaluated ethylbenzene and classified it as a possible human carcinogen (Group 2B) based on sufficient evidence for carcinogenicity in experimental animals, but inadequate evidence for cancer in exposed humans. Chronic effects of ingestion and subsequent aspiration into the lungs may cause pneumatocele (lung cavity) formation and chronic lung dysfunction. Significant exposure to this chemical may adversely affect people with chronic disease of the respiratory system, skin, and/or eyes. Significant exposure to this chemical may adversely affect people with chronic disease of the central nervous system.

Primary Route(s) of Entry: Eye Contact, Ingestion, Inhalation, Skin Absorption, Skin Contact

Safety Data Sheet

According to OSHA Hazard Communication 29 CFR Part 1910.1200

Version: 1.0

Revision: 3/15/21

Trade Name: AUS-50™ – ALIPHATIC URETHANE SEALER

Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below:

<u>CAS-No.</u>	<u>Name according to EEC</u>	<u>Oral LD50, mg/kg</u>	<u>Dermal LD50, mg/kg</u>	<u>Vapor LC50, mg/L</u>
1330-20-7	Xylene	>3523	>4200	>20.0

SECTION 12 Ecological information

ECOLOGICAL INFORMATION: No Information

SECTION 13 Disposal considerations





For more guidance and information contact our Waste Services Division at (262) 658-4000. Always dispose of any waste in accordance with all local, state, and federal regulations.

DISPOSAL METHOD: Dispose of waste in accordance with all local, state and federal regulations.

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Wear appropriate personal protective equipment. (See Exposure Controls / Personal Protection Section.) Eliminate all ignition sources. Prevent additional discharge of material if able to do so safely. Do not touch or walk through spilled material. Avoid runoff into storm sewers and ditches which lead to waterways. Ventilate spill area. Stay upwind of spill. A vapor suppressing foam may be used to reduce vapors. Collect spilled materials for disposal. Use only non-combustible material for clean-up. Use clean, non-sparking tools to collect absorbed materials. Remove from surface by skimming or with suitable absorbents. Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container.

SECTION 14 Transport information

14.1 UN-Number	
DOT:	UN 1263
ADR, IMDG, IATA:	UN 1263
14.2 UN proper shipping name	
DOT:	Resin Solution
ADR, IMDG, IATA:	Resin Solution
14.3 Transport hazard class(es)	
DOT	
Class:	3
Label:	
ADR, IMDG, IATA	
Class:	Class 3
Label:	

Safety Data Sheet

According to OSHA Hazard Communication 29 CFR Part 1910.1200

Version: 1.0

Revision: 3/15/21

Trade Name: AUS-50™ – ALIPHATIC URETHANE SEALER

14.4 Packing group

DOT, ADR, IMDG, IATA: PG III

SECTION 15 Regulatory information

U.S. Federal Regulations:

CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

<u>Chemical Name</u>	<u>CAS-No.</u>
Xylene	1330-20-7

TOXIC SUBSTANCES CONTROL ACT:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA components exist in this product.

U.S. State Regulations:

NEW JERSEY RIGHT-TO-KNOW:

The following materials are non-hazardous, but are among the top five components in this product.

No NJ Right-To-Know components exist in this product.

PENNSYLVANIA RIGHT-TO-KNOW

The following non-hazardous ingredients are present in the product are at or greater than 3%.

No PA Right-To-Know components exist in this product.

CALIFORNIA PROPOSITION 65 CARCINOGENS

Warning: The following ingredients present in the product are known to the state of California to cause Cancer:

CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS

Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

No Proposition 65 Reproductive Toxins exist in this product.

International Regulations: As follows -

CANADIAN WHMIS:

This MSDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

WHMIS Class: No Information

Safety Data Sheet

According to OSHA Hazard Communication 29 CFR Part 1910.1200

Version: 1.0

Revision: 3/15/21

Trade Name: AUS-50™ – ALIPHATIC URETHANE SEALER

SECTION 16 Other information

Revision Date: 12/22/2014 **Supersedes Date:** New SDS

Datasheet produced by: Elite Crete Systems

HMIS Ratings:

Health:	2	Flammability:	3	Reactivity:	0	Personal Protection:	X
----------------	---	----------------------	---	--------------------	---	-----------------------------	---

Volatile Organic Compounds, gr/ltr: 400

DISCLAIMER: THE VOLATILE ORGANIC COMPOUND (VOC) CONTENT REPORTED HEREIN, IF ANY, IS BASED ON A MATERIAL VOC CALCULATION. NOTE THAT SEVERAL METHODS ARE USED FOR CALCULATING VOC CONTENT AND THAT STANDARDS/ REQUIREMENTS REGARDING VOC CONTENT VARY BY LOCATION/JURISDICTION. ACCORDINGLY, EMCO MAKES NO REPRESENTATIONS OR WARRANTIES, EXPRESS OR IMPLIED, REGARDING THIS MATERIAL'S COMPLIANCE WITH VOC STANDARDS/REQUIREMENTS APPLICABLE IN LOCATIONS/JURISDICTIONS WHERE THIS MATERIAL MAY BE SOLD OR USED.

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H225	Highly flammable liquid and vapor.
H226	Flammable liquid and vapor.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.

GHS PRECAUTIONARY STATEMENTS

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P260	Do not breathe dust/fume/gas/mist/vapors/spray.
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician
P302+P352	IF ON SKIN: Wash with plenty of water
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove

Safety Data Sheet

According to OSHA Hazard Communication 29 CFR Part 1910.1200

Version: 1.0

Revision: 3/15/21

Trade Name: AUS-50™ – ALIPHATIC URETHANE SEALER

P308+P313	contact lenses, if present and easy to do. Continue rinsing.
P312	IF exposed or concerned: Get medical advice/attention.
P314	Call a POISON CENTER/doctor/physician if you feel unwell.
P321	Get medical advice/attention if you feel unwell.
P331	Specific treatment (see first aid section on this label).
P332+P313	Do NOT induce vomiting.
P337+P313	If skin irritation occurs: Get medical advice/attention.
P362+P364	If eye irritation persists: Get medical advice/attention.
P370+P378	Take off contaminated clothing and wash it before reuse.
P403+P233	In case of fire: Use appropriate method to extinguish.
P403+P235	Store in a well-ventilated place. Keep container tightly closed.
P405	Store in a well-ventilated place. Keep cool.
P501	Store locked up.
	Dispose of contents/container in accordance with local/regional/national/international regulations.

Icons for GHS Pictograms shown in Section 3 describing each ingredient:

GHS02	
GHS07	
GHS08	

Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined, N.I. - No Information

The information on this SDS was obtained from sources which we believe to be reliable. However, the information provided is without any warranty, expressed or implied, regarding its correctness. Some information presented and conclusions drawn herein are from sources other than direct test data on the product itself. The information and recommendations are offered for the user's consideration and examination and should be used to make an independent determination of the methods to safeguard workers and the environment. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For these reasons we do not assume responsibility and expressly disclaim any liability for loss, damage, or expense arising out of or in any way connected with handling, storage, use, or disposal of this product. If the product is used as a component in another product, this SDS may not be applicable. It is the responsibility of the user to comply with all Federal, State, and Local laws and regulations.