

Safety Data Sheet

According to 1907/2006/EC (REACH) and 1272/2008/EC (CLP)

Version: 1.2

Revision: 6/14/21

Trade Name: E100-PT1™ CRYSTAL CLEAR EPOXY – Part A**1 Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier**

Trade Name: E100-PT1™ Part A

1.2 Article No.: E100-PT1™ Part A**1.3 Details of the supplier of the Safety Data Sheet Manufacturer:**

Elite Crete Systems
 1151 Transport Drive
 Valparaiso, IN 46383
 Toll Free: 888.323.4445
 Tel: (219) 465-7671
www.elitecrete.com

1.4 Emergency telephone number:

CHEMTREC US DOMESTIC: (800-424-9300)
 CHEMTREC INTERNATIONAL: (703-527-3887)

2 Hazards identification**2.1 Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008 and GHS:**

The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H361fd, H411.

The following Hazard Statements are applicable only according to OSHA regulations within the United States. These Statements are not applicable for the CLP regulation (1272/2008/EC) in the EU: H361.

Skin Irrit. 2 H-315: Causes skin irritation
 Eye Damage 1; H318: Causes serious eye damage.

**GHS09 environment**

Aquatic Chronic 2; H411: Toxic to aquatic life with long lasting effects.

**GHS07 exclamation mark**

*Acute Tox. 2; H302: Harmful if swallowed.
 Skin Sensitization 1; H317: May cause an allergic skin reaction. STOT SE 3; H335: May cause respiratory irritation.*

Classification according to Directive 67/548/EEC or Directive 1999/45/EC:

Xn; Harmful. R22-62: Harmful if swallowed. Possible risk of impaired fertility. Xi; Sensitizing. R43: May cause sensitization by skin contact
 Xi; Irritant. R37: Irritating to respiratory system. R22-48: Harmful if swallowed.
 N; Dangerous for the environment. R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Information concerning particular hazards for human and environment:

The product has to be labeled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

Safety Data Sheet

According to 1907/2006/EC (REACH) and 1272/2008/EC (CLP)

Version: 1.2


Revision: 6/14/21

Trade Name: E100-PT1™ CRYSTAL CLEAR EPOXY – Part A

2.2 Label elements

Labeling according to Regulation (EC) No 1272/2008:

Hazard pictograms:



GHS07 GHS09

Signal Word: Warning

Hazard-determining components of labeling:

Bisphenol A based Epoxy Resin, Alkyl C-12-C-14 Glycidyl Ether

Hazard statements

- H312: Harmful in contact with skin
- H317: May cause an allergic skin reaction
- H412: Harmful to aquatic life with long lasting effects

Precautionary statements

- P264: Wash hands thoroughly after handling
- P270: Do not eat, drink or smoke when using this product
- P271: Use only in well ventilated area.
- P273: Avoid release to the environment
- P280: Wear protective gloves/protective clothing/eye protection/face protection
- P337+P313: If eye irritation persists: Get medical advice/attention.
- P370+P378: In case of fire: Use for extinction: CO2, powder or water spray.
- P302+P352: IF ON SKIN: Wash with plenty of soap and water.
- P391: Collect spillage.
- P403+P235: Store in a well-ventilated place. Keep cool.
- P501: Dispose of contents/container in accordance with local/regional/national/international regulations

2.3 Other hazards

Results of PBT and vPvB assessment:

PBT: Not applicable.

vPvB: Not applicable.

Hazard description:

Canadian WHMIS Classification: This product is categorized as a Class D Division 2B Materials causing other toxic effects, as per the Controlled Product Regulations

WHMIS-symbols:



NFPA ratings (scale 0 - 4)



Health = 2
Fire = 1
Reactivity = 0

HMIS-ratings (scale 0 - 4)

**Safety Data Sheet**

According to 1907/2006/EC (REACH) and 1272/2008/EC (CLP)

Version: 1.2

Revision: 6/14/21

Trade Name: E100-PT1™ CRYSTAL CLEAR EPOXY – Part A

Health	2
Fire	1
Reactivity	0

Health = 2
Fire = 1
Reactivity = 0

2.3 Other hazards
No known

3 Composition/information on ingredients**3.2 Mixture.****Description:** Mixture of substances listed below with nonhazardous additives.**Hazardous components:**

Identification #	Description	WT. %
CAS: 25085-99-8 EINECS: Not Listed Index Number:	Bisphenol A based Epoxy Resin HAZARD CLASSIFICATION: [Xn] Harmful, [Xi] Irritant RISK PHRASES: R21, R34, R43, R52/53	< 85-92%
CAS: 68609-97-2 EINECS: 271-846-8 Index Number;	Alkyl C-12-C-14 Glycidyl Ether Skin Irritant 1, Skin Sens. 1, Muta. 2; Aquatic Chronic 2; R 43; Xi 38; R 38, R43.	< 8-15%

Additional information: Balance of other ingredients are non-hazardous or less than 1% in concentration (or 0.1% for carcinogens, reproductive toxins, or respiratory sensitizers).



Safety Data Sheet

According to 1907/2006/EC (REACH) and 1272/2008/EC (CLP)

Version: 1.2

Revision: 6/14/21

Trade Name: E100-PT1™ CRYSTAL CLEAR EPOXY – Part A

4 First aid measures

4.1 Description of first aid measures

After inhalation:

If breathing becomes difficult, remove victim to fresh air. If necessary, use artificial respiration to support vital functions. Seek medical attention if breathing difficulty continues.

After skin contact:

Wash skin thoroughly after handling. Seek medical attention if irritation develops and persists. Remove contaminated clothing. Launder contaminated clothing before re-use.

After eye contact:

If product enters the eyes, open eyes while under gentle running water for at least 15 minutes. Seek medical attention.

After swallowing:

If product is swallowed, call physician or poison control center for most current information. If professional advice is not available, do not induce vomiting. Never induce vomiting or give diluents (milk or water) to someone who is unconscious, having convulsions, or who cannot swallow. Seek medical advice. Take a copy of the label and/or MSDS with the victim to the health professional.

4.2 Most important symptoms and effects, both acute and delayed.

Acute: This material may cause irritation to skin and eyes. Product may cause an allergic skin reaction.

Chronic: Prolonged or repeated skin contact may cause allergic skin reaction or dermatitis.

Target Organs: **Acute:** Eye, Skin **Chronic:** Skin

Hazards: Pre-existing skin or eye problems may be aggravated by exposure to this product.

4.3 Indication of any immediate medical attention and special treatment needed:

Treat symptoms and reduce over-exposure.

5 Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents: Carbon dioxide, foam, dry chemical, halon, water spray, sand, limestone powder.

5.2 Special hazards arising from the substance or mixture:

This product is a flammable liquid above flash point shown.

5.3 Advice for firefighters:

Incipient fire responders should wear eye protection. Structural firefighters must wear Self-Contained Breathing Apparatus and full protective equipment. Isolate materials not yet involved in the fire and protect personnel. Move containers from fire area if this can be done without risk; otherwise, cool with carefully applied water spray. If possible, prevent runoff water from entering storm drains, bodies of water, or other environmentally sensitive areas.

6 Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

Personnel should be trained for spill response operations.

6.2 Environmental precautions:

All work practices must be aimed at eliminating environmental contamination.

6.3 Methods and material for containment and cleaning up:

Evacuate area. Contain spill if safe to do so. Prevent entry into drains, sewers, and other waterways. Soak up spilled material with an absorbent material and pick up and place in an appropriate waste container for disposal. Do not mix with other wastes. Dispose of in accordance with applicable Federal, State, and local procedures (see Section 13, Disposal Considerations).



Safety Data Sheet

According to 1907/2006/EC (REACH) and 1272/2008/EC (CLP)

Version: 1.2

Revision: 6/14/21

Trade Name: E100-PT1™ CRYSTAL CLEAR EPOXY – Part A

7 Handling and storage

7.1 Precautions for safe handling

As with all chemicals, avoid getting this product ON YOU or IN YOU. Wash thoroughly after handling this product. Do not eat, drink, smoke, or apply cosmetics while handling this product. Avoid breathing vapors/mists generated by this product. Use in a well-ventilated location. Remove contaminated clothing immediately.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Store between 10 and 50 0C (45 -125 0F) and avoid contact with skin and eyes. Do not store near acids or amines. Ground all transfer equipment. Good general housekeeping procedure should be followed. Do not eat drink or smoke while using the material. Emergency showers should be readily available. Material may partially freeze in cold temperatures which will result in crystals and haziness. If this occurs rewarm and homogenize. Avoid contact with skin eyes. Vapors may irritate eyes and will irritate the skin. Use only with good ventilation and PPE. Keep container closed when not in use.

7.3 Specific end use(s): No information

8 Exposure controls/personal protection

Additional information about design of technical facilities:



Use with adequate ventilation to ensure exposure levels are maintained below the limits provided above.

Use local exhaust ventilation to control airborne vapor. Ensure eyewash/safety shower stations are available near areas where this product is used.

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

Currently, International exposure limits are not established for the components of this product. Please check with competent authority in each country for the most recent limits in place.

8.2 Exposure controls

Personal protective equipment:

General protective and hygienic measures:

The following information on appropriate Personal Protective Equipment is provided to assist employers in complying with OSHA regulations found in 29 CFR Subpart I (beginning at 1910.132) or equivalent standard of Canada, or standards of EU member states (including EN 149 for respiratory PPE, and EN 166 for face/eye protection), and those of Japan. Please reference applicable regulations and standards for relevant details.

Respiratory protection: Maintain airborne contaminant concentrations below guidelines listed above, if applicable. If necessary, use only respiratory protection authorized in the U.S. Federal OSHA Respiratory Protection Standard (29 CFR 1910.134), equivalent U.S. State standards, Canadian CSA Standard Z94.4-93, the European Standard EN149, or EU member states.

Protection of hands: Use chemical resistant gloves to prevent skin contact. If necessary, refer to U.S. OSHA 29 CFR 1910.138 or appropriate Standards of Canada.

Protective gloves

Material of gloves:

The selection of suitable gloves does not only depend on the material, but also on the quality, and varies from manufacturer to manufacturer.

Penetration time of glove material:

The exact break through time has to be determined by the manufacturer of the protective gloves. DO NOT exceed the breakthrough time set by the Manufacturer.



**Safety Data Sheet**

According to 1907/2006/EC (REACH) and 1272/2008/EC (CLP)

Version: 1.2

Revision: 6/14/21

Trade Name: E100-PT1™ CRYSTAL CLEAR EPOXY – Part A

Eye protection: Safety glasses or chemical goggles as appropriate to prevent eye contact. If necessary, refer to U.S. OSHA 29 CFR 1910.133 or appropriate Canadian Standards.

Tightly sealed goggles

Body Protection:

Use body protection appropriate to prevent contact (e.g. lab coat, overalls). If necessary, refer to appropriate Standards of Canada, or appropriate Standards of the EU, Australian Standards, or relevant Japanese Standards.

9 Physical and chemical properties**9.1 Information on basic physical and chemical properties****General Information****Appearance:****Form:**

Liquid

Color:

Clear – Slight amber haze

Odor:

Mild epoxy odor

Odor threshold:

Not Available

pH-value:

Not Available

Change in condition**Melting point/Melting range:**

No data available

Boiling point/Boiling range:

>200°C

Flash point:

>392°F (>200°C)

Flammability (solid, gaseous):

No data available

Auto/Self-ignition temperature:

Not established

Decomposition temperature:

No data available

Self-igniting:

No data available

Danger of explosion:

This product is a flammable liquid above flash point shown above.

Explosion limits**Lower:**

Not established

Upper:

Not established

Vapor pressure at 25 °C:

<0.1 mmHg

Density at 20°C:

9.45 lbs. per gallon, specific gravity 1.13

Relative density:

No data available

Vapor density:

No data available

Evaporation rate:

No data available

Solubility in / Miscibility with Water:

Not Available

Specific Gravity 20oC: (Water = 1):

Not Available

Viscosity:**Dynamic:**

No data available



Safety Data Sheet

According to 1907/2006/EC (REACH) and 1272/2008/EC (CLP)

Version: 1.2

Revision: 6/14/21

Trade Name: E100-PT1™ CRYSTAL CLEAR EPOXY – Part A

Kinematic:	No data available
Solvent content:	
Organic solvents:	No data available
VOC (EC)	No data available
9.2 Other information	No data available

10 Stability and reactivity

10.1 Reactivity**10.2 Chemical stability:** Product is stable

Thermal decomposition / conditions to be avoided: When heated to decomposition this product produces noxious gases such as CO, CO₂, hydrocarbons and soot.

10.3 Possibility of hazardous reactions: No data available**10.4 Conditions to avoid:** Contact with incompatible materials**10.5 Incompatible materials:** Oxidizing agents and amines should be avoided as these will cause exothermic polymerization. Avoid extreme heat**10.6 Hazardous decomposition products:** Will not occur

11 Toxicological information

11.1 Information on toxicological effects: Toxicity data is available for this product**Acute toxicity:**

Acute Dermal	LD 50	>20,000 mg/kg	Rabbit
Acute Oral	LD 50	>5,000 mg/kg	Rat

Primary irritant effect: Contact with this product can be irritating to exposed skin and eyes.

Sensitization: This product is considered a skin sensitizer.

Additional toxicological information:

None of the ingredients are found on the following lists: FEDERAL OSHA Z LIST, NTP, CAL/OSHA, IARC and therefore is not considered to be, nor suspected to be a cancer-causing agent by these agencies.

Reproductive toxicity information:

No information concerning the effects of this product and its components on the human reproduction system.



Safety Data Sheet

According to 1907/2006/EC (REACH) and 1272/2008/EC (CLP)

Version: 1.2

Revision: 6/14/21

Trade Name: E100-PT1™ CRYSTAL CLEAR EPOXY – Part A

12 Ecological information

12.1 Toxicity

Aquatic toxicity: No evidence is currently available on this product's effects on aquatic life.

Component Data: CAS# 25085-99-8

Fathead Minnow LC50 3 mg/l 96 h

Toxicity to daphnia magna EC50 1.4 -1.7 mg/l 24 h

Bacteria: IC50 >42.6 mg/l 18 h

Biodegradation: 28 days 12% OECD

Bioaccumulation: Not readily biodegradable

12.2 Persistence and degradability: No data available

12.3 Bio accumulative potential: No data available

12.4 Mobility in soil: No evidence is currently available on this product's effects on plants or animals.

Ecotoxicological effects:

Remark:

Additional ecological information: No data available

General notes: No specific data is available for this product; however, this product is expected to be readily biodegradable

13 Disposal considerations

13.1 Waste treatment methods

Recommendations:

Waste disposal must be in accordance with appropriate Federal, State, and local regulations, those of Canada, Australia, EU Member States and Japan.

RCRA WASTE CODE: None Listed

EU WASTE CODE: Not Listed

14 Transport information

14.1 UN-Number

DOT: CAN:

NOT REGULATED

ADN: ADR: IMDG: IATA:

UN 3082

14.2 UN proper shipping name

DOT: CAN:

NOT REGULATED

ADN: ADR: IMDG: IATA:

Environmentally Hazardous Substance liquid,
N.O.S. (Bisphenol A epoxy resin)

14.3 Transport hazard class(es)

DOT: CAN:



ADR: ADN: IMDG: IATA



14.4 Packing group

DOT: CAN:

NOT REGULATED


**Safety Data Sheet**

According to 1907/2006/EC (REACH) and 1272/2008/EC (CLP)

Version: 1.2

Revision: 6/14/21

Trade Name: E100-PT1™ CRYSTAL CLEAR EPOXY – Part A

ADN: ADR: IMDG: IATA	PG III
14.5 Environmental hazards	Product contains environmentally hazardous substances: reaction Products of Epichlorohydrin and Bisphenol A)
Marine Pollutant:	YES
Special Marking (ADR):	 Notes: marine pollutant (IMDG code 2.9.3). For air transport, see special provision A97. (ICAO/IATA). For surface shipments within the USAL Not Regulated.
14.6 Special precautions for user	
Danger code (Kemler):	NOT APPLICABLE
EMS Number:	
14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:	NOT APPLICABLE
Transport/Additional information	
ADR	
Tunnel restriction code	NOT APPLICABLE
UN "Model Regulation":	NOT APPLICABLE

15 Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture. United States (USA)**

SARA: This product is not subject to the reporting requirements of Sections 302, 304 and 313 of Title III of the Superfund Amendments and Reauthorization Act.: None

Section 355 (extremely hazardous substances): None of the ingredients are listed.

Section 313 (Toxic Release Inventory): None of the ingredients are listed.

TSCA (Toxic Substances Control Act): All ingredients are listed.

Proposition 65 (California):**Chemicals known to cause cancer:**

None of the ingredients is listed.

Canada**Canadian Domestic Substances List (DSL):**

All ingredients are listed

Canadian Ingredient Disclosure list (limit 0.1%):

None of the ingredients are listed.

Canadian Ingredient Disclosure list (limit 1%):

None of the ingredients are listed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.



Safety Data Sheet

According to 1907/2006/EC (REACH) and 1272/2008/EC (CLP)

Version: 1.2

Revision: 6/14/21

Trade Name: E100-PT1™ CRYSTAL CLEAR EPOXY – Part A

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases:

H312: Harmful in contact with skin

H317: May cause an allergic skin reaction

H412: Harmful to aquatic life with long lasting effects

R21: Harmful in contact with skin

R34: Causes burns

R43: May cause sensitization by skin contact.

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment

Abbreviations and acronyms:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation.

IATA: International Air Transport Association.

ACGIH: American Conference of Governmental Industrial Hygienists.

EINECS: European Inventory of Existing Commercial Chemical Substances.

ELINCS: European List of Notified Chemical Substances.

CAS: Chemical Abstracts Service (division of the American Chemical Society).

NFPA: National Fire Protection Association (USA).

HMIS: Hazardous Materials Identification System (USA).

LC50: Lethal concentration, 50 percent.

LD50: Lethal dose, 50 percent.