

# Safety Data Sheet

According to OSHA Hazard Communication 29 CFR Part 1910.1200

Version: 1.2

Revision: 4/26/2022

**Trade Name: CSS EMULSION™ - VINTAGE**

## SECTION 1 Identification

Product Type:: Solvent Based Sealer  
 Product Name: CSS EMULSION™ - VINTAGE  
 Supplied by:  
 Elite Crete Systems  
 1151 Transport Drive  
 Valparaiso, IN 46383  
 Toll Free: 888.323.4445  
 Tel: (219) 465-7671  
[elitecrete.com](http://elitecrete.com)

### For Emergency Medical Assistance:

Call Health & Safety Information Services

(1-866-303-6949)

For Emergency transportation Information:

CHEMTREC US DOMESTIC: 1-800-424-9300

CHEMTREC INTERNATIONAL: 1-703-527-3887

## SECTION 2 Hazard(s) identification

\*\*\* **EMERGENCY OVERVIEW** \*\*\*: Flammable liquid and vapor. May be fatal if swallowed. Suspect cancer hazard.

### GHS Classification

Acute Tox. 4, Asp. Tox. 1, Carc. 2, Eye Irrit. 2, Flam. Liq. 3, STOT RE 2, STOT SE 3 RTI, Skin Irrit. 2

### NFPA ratings (scale 0 - 4)



Health = 2  
 Fire = 3  
 Reactivity = 0

### HMIS-ratings (scale 0 - 4)

|            |   |
|------------|---|
| Health     | 2 |
| Fire       | 3 |
| Reactivity | 0 |

Health = 2  
 Fire = 3  
 Reactivity = 0  
 Personal Protection = X

### Symbol(s) of Product



### Signal Word

Danger

### GHS HAZARD STATEMENTS

|  |   |
|--|---|
| Flammable Liquid, category 3           | H226 Flammable liquid and vapor.  |
| Aspiration Hazard, category 1          | H304 May be fatal if swallowed and enters airways.                      |
| Skin Irritation, category 2            | H315 Causes skin irritation.  |
| Eye Irritation, category 2             | H319 Causes serious eye irritation.                                     |
| Acute Toxicity, Inhalation, category 4 | H332 Harmful if inhaled.  |
| STOT, single exposure, category 3, RTI | H335 May cause respiratory irritation.                                  |
| Carcinogenicity, category 2            | H351 Suspected of causing cancer.                                       |
| STOT, repeated exposure, category 2    | H373 May cause damage to organs through prolonged or repeated exposure. |

# Safety Data Sheet

According to OSHA Hazard Communication 29 CFR Part 1910.1200

Version: 1.2

Revision: 4/26/2022

|  |
|--|
| <b>Trade Name: CSS EMULSION™ - VINTAGE</b> |
|--|

## GHS PRECAUTIONARY STATEMENTS

|                |  |
|----------------|--|
| P201           | Obtain special instructions before use.  |
| P202           | Do not handle until all safety precautions have been read and understood.  |
| P210           | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.                                   |
| P240           | Ground/bond container and receiving equipment.   |
| P241           | Use explosion-proof electrical/ventilating/lighting/equipment.   |
| P242           | Use only non-sparking tools.   |
| P243           | Take precautionary measures against static discharge.  |
| P260           | Do not breathe dust/fume/gas/mist/vapors/spray.  |
| P264           | Wash thoroughly after handling.  |
| P271           | Use only outdoors or in a well-ventilated area.  |
| P280           | Wear protective gloves/protective clothing/eye protection/face protection.   |
| P301+P310      | IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician  |
| P302+P352      | IF ON SKIN: Wash with plenty of water  |
| P303+P361+P353 | IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.                              |
| P304+P340      | IF INHALED: Remove person to fresh air and keep comfortable for breathing.   |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P308+P313      | IF exposed or concerned: Get medical advice/attention.   |
| P312           | Call a POISON CENTER/doctor/physician if you feel unwell.  |
| P314           | Get medical advice/attention if you feel unwell.   |
| P321           | Specific treatment (see first aid section on this label).  |
| P331           | Do NOT induce vomiting.  |
| P332+P313      | If skin irritation occurs: Get medical advice/attention.   |
| P337+P313      | If eye irritation persists: Get medical advice/attention.  |
| P362+P364      | Take off contaminated clothing and wash it before reuse.   |
| P370+P378      | In case of fire: Use appropriate method to extinguish.   |
| P403+P233      | Store in a well-ventilated place. Keep container tightly closed.   |
| P403+P235      | Store in a well-ventilated place. Keep cool.   |
| P405           | Store locked up.   |
| P501           | Dispose of contents/container in accordance with local/regional/national/international regulations.                              |

## SECTION 3 Composition/information on ingredients

| <u>Chemical Name</u> | <u>CAS-No.</u> | <u>WT. %</u> | <u>GHS Symbols</u> | <u>GHS Statements</u>        |
|----------------------|----------------|--------------|--------------------|------------------------------|
| Xylene               | 1330-20-7      | 49%          | GHS02-GHS07-GHS08  | H226-315-319-332-335-351-373 |
| Ethylbenzene         | 100-41-4       | 51%          | GHS02-GHS07-GHS08  | H225-315-319-332-335-351-373 |

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

# Safety Data Sheet

According to OSHA Hazard Communication 29 CFR Part 1910.1200

Version: 1.2

Revision: 4/26/2022

Trade Name: CSS EMULSION™ - VINTAGE

## SECTION 4 First aid measures



**FIRST AID - EYE CONTACT:** Immediately flush eyes with water. Flush eyes with water for a minimum of 15 minutes, occasionally lifting and lowering upper lids. Get medical attention promptly. Remove contact lenses if worn.

**FIRST AID - SKIN CONTACT:** Remove contaminated clothing. Wash skin with soap and water. Get medical attention. Wash clothing separately and clean shoes before reuse.

**FIRST AID - INHALATION:** Rescuers should put on appropriate protective gear. Remove from area of exposure. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Keep victim warm. Get immediate medical attention. To prevent aspiration, keep head below knees.

**FIRST AID - INGESTION:** DO NOT induce vomiting. DO NOT give liquids. Get medical attention immediately.

## SECTION 5 Firefighting measures

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Flammable liquid and vapor. Vapors/dust may form explosive mixture with air. Vapors can travel to a source of ignition and flash back. Empty containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. Also, do not reuse container without commercial cleaning or reconditioning. Closed container may explode under extreme heat.

**SPECIAL FIREFIGHTING PROCEDURES:** As in any fire, wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear. Avoid use of solid water streams. Use water with caution. Material will float and may ignite on surface of water. Water may be ineffective in fighting the fire. Water spray to cool containers or protect personnel. Use with caution. Water runoff can cause environmental damage. Dike and collect water used to fight fire.

**EXTINGUISHING MEDIA:** Carbon Dioxide, Dry Chemical, Foam, Water Fog

## SECTION 6 Accidental release measures

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** Wear appropriate personal protective equipment. (See Exposure Controls / Personal Protection Section.) Eliminate all ignition sources. Prevent additional discharge of material if able to do so safely. Do not touch or walk through spilled material. Avoid runoff into storm sewers and ditches which lead to waterways. Ventilate spill area. Stay upwind of spill. A vapor suppressing foam may be used to reduce vapors. Collect spilled materials for disposal. Use only non-combustible material for clean-up. Use clean, non-sparking tools to collect absorbed materials. Remove from surface by skimming or with suitable absorbents. Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container.

## SECTION 7 Handling and storage



**HANDLING:** Use only in a well ventilated area. Avoid breathing vapor, fumes or mist. Avoid contact with eyes, skin, and clothing. Material accumulates static charge (ignition source). When transferring, follow proper grounding procedures. Use spark-resistant tools. Do not load into compartments adjacent to heated cargo. Use explosion proof equipment. Always open containers slowly to allow any excess pressure to vent. Follow all MSDS/label precautions even after containers are emptied because they may retain product residues.

**STORAGE:** Keep away from heat, sparks, and flame. Containers can build up pressure if exposed to heat (fire).

# Safety Data Sheet

According to OSHA Hazard Communication 29 CFR Part 1910.1200

Version: 1.2

Revision: 4/26/2022

## Trade Name: CSS EMULSION™ - VINTAGE

Store containers in a cool, well ventilated place. Keep container closed when not in use. Protect from direct sunlight. Material is a static accumulator which has the potential of forming ignitable vapor-air mixtures in storage tanks

## SECTION 8 Exposure controls/personal protection

### Ingredients with Occupational Exposure Limits

| <u>Chemical Name</u> | <u>ACGIH TLV-TWA</u> | <u>ACGIH-TLV STEL</u> | <u>OSHA PEL-TWA</u> | <u>OSHA PEL-CEILING</u> |
|----------------------|----------------------|-----------------------|---------------------|-------------------------|
| Acrylic Polymer (s)  | None                 | None                  | None                | N.D.                    |
| Xylene               | 100 ppm              | 150ppm                | 100 ppm             | N.D.                    |
| Ethylbenzene         | 100 ppm              | 125 ppm               | 100 ppm             | N.D.                    |

### Personal Protection



**RESPIRATORY PROTECTION:** NIOSH/MSHA approved respirators may be necessary if airborne concentrations are expected to exceed exposure limits.



**SKIN PROTECTION:** Wear impervious gloves to prevent contact with the skin. Wear protective gear as needed - apron, suit, boots.



**EYE PROTECTION:** Wear safety glasses with side shields (or goggles) and a face shield.



**OTHER PROTECTIVE EQUIPMENT:** Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.



**HYGIENIC PRACTICES:** Do not eat, drink, or smoke in areas where this material is used. Avoid breathing vapors. Remove contaminated clothing and wash before reuse. Wash thoroughly after handling. Wash hands before eating.

## SECTION 9 Physical and chemical properties

|                                   |                           |                                 |           |
|-----------------------------------|---------------------------|---------------------------------|-----------|
| <b>Appearance:</b>                | Clear, transparent liquid | <b>Physical State:</b>          | Liquid    |
| <b>Odor:</b>                      | Typical                   | <b>Odor Threshold:</b>          | N.D.      |
| <b>Density, g/cm<sup>3</sup>:</b> | 0.872                     | <b>pH:</b>                      | N.D.      |
| <b>Freeze Point, °F:</b>          | N.D.                      | <b>Viscosity:</b>               | N.D.      |
| <b>Solubility in Water:</b>       | Insoluble                 | <b>Explosive Limits, vol%:</b>  | 1.0 – 7.0 |
| <b>Boiling Range, °F:</b>         | 277 – 288                 | <b>Flash Point, °F:</b>         | 81        |
| <b>Evaporation Rate:</b>          | 0.8 (n-Bu Acetate=1)      | <b>Auto-ignition Temp., °F:</b> | N.D.      |
| <b>Vapor Density:</b>             | 3 (air=1)                 | <b>Vapor Pressure:</b>          | 7mm Hg    |

## SECTION 10 Stability and reactivity

**STABILITY:** No Information

**CONDITIONS TO AVOID:** Avoid impact, friction, heat, sparks, flame and source of ignition.

**INCOMPATIBILITY:** Keep separate from alkalies. Keep away from acids. Prevent contact with oxidizing materials.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Toxic gases/fumes are given off during burning or thermal

# Safety Data Sheet

According to OSHA Hazard Communication 29 CFR Part 1910.1200

Version: 1.2

Revision: 4/26/2022

## Trade Name: CSS EMULSION™ - VINTAGE

decomposition. During combustion carbon monoxide may be formed. During combustion carbon dioxide may be formed.

### SECTION 11 Toxicological information



**HAZARDOUS POLYMERIZATION:** No Information

#### Information on Toxicological Effects

**EFFECTS OF OVEREXPOSURE - INHALATION:** Breathing saturated vapors for a few minutes may be fatal.

Saturated vapors can be encountered in confined spaces and/or under conditions of poor ventilation. Prolonged inhalation may be harmful. Vapors can cause irritation of the respiratory tract. High concentrations can cause headache, nausea, weakness, lightheadedness, and stupor (CNS depression). May cause dizziness and drowsiness.

**EFFECTS OF OVEREXPOSURE - SKIN CONTACT:** Contact with skin may cause mild irritation. Can be absorbed through skin and produce central nervous system effects. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash). Personnel with pre-existing skin disorders should avoid contact with this product. can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

**EFFECTS OF OVEREXPOSURE - EYE CONTACT:** May cause eye irritation. Symptoms may include stinging, tearing, redness and swelling.

**EFFECTS OF OVEREXPOSURE - INGESTION:** May be fatal if swallowed. Aspiration hazard if swallowed - can enter lungs and cause damage. Ingestion may cause gastrointestinal tract irritation. May cause nausea and diarrhea.

**EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS:** Suspect cancer hazard. Possible brain damage from overexposure. The International Agency for Research on Cancer has evaluated ethylbenzene and classified it as a possible human carcinogen (Group 2B) based on sufficient evidence for carcinogenicity in experimental animals, but inadequate evidence for cancer in exposed humans. Chronic effects of ingestion and subsequent aspiration into the lungs may cause pneumatocele (lung cavity) formation and chronic lung dysfunction. Significant exposure to this chemical may adversely affect people with chronic disease of the respiratory system, skin, and/or eyes. Significant exposure to this chemical may adversely affect people with chronic disease of the central nervous system.

**Primary Route(s) of Entry:** Eye Contact, Ingestion, Inhalation, Skin Absorption, Skin Contact

#### Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below:

| <u>CAS-No.</u> | <u>Name according to EEC</u> | <u>Oral LD50, mg/kg</u> | <u>Dermal LD50, mg/kg</u> | <u>Vapor LC50, mg/L</u> |
|----------------|------------------------------|-------------------------|---------------------------|-------------------------|
| 1330-20-7      | Xylene                       | >3523                   | >4200                     | >20.0                   |
| 100-41-4       | Ethylbenzene                 | 3500                    | 15433                     | >20.0                   |

### SECTION 12 Ecological information

**ECOLOGICAL INFORMATION:** No Information

# Safety Data Sheet

According to OSHA Hazard Communication 29 CFR Part 1910.1200

Version: 1.2

Revision: 4/26/2022

Trade Name: CSS EMULSION™ - VINTAGE

## SECTION 13 Disposal considerations





For more guidance and information contact our Waste Services Division at (262) 658-4000. Always dispose of any waste in accordance with all local, state, and federal regulations.

**DISPOSAL METHOD:** Dispose of waste in accordance with all local, state and federal regulations.

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** Wear appropriate personal protective equipment. (See Exposure Controls / Personal Protection Section.) Eliminate all ignition sources. Prevent additional discharge of material if able to do so safely. Do not touch or walk through spilled material. Avoid runoff into storm sewers and ditches which lead to waterways. Ventilate spill area. Stay upwind of spill. A vapor suppressing foam may be used to reduce vapors. Collect spilled materials for disposal. Use only non-combustible material for clean-up. Use clean, non-sparking tools to collect absorbed materials. Remove from surface by skimming or with suitable absorbents. Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container.

## SECTION 14 Transport information

|  |   |
|--|---|
| <b>14.1 UN-Number</b>                  |   |
| DOT:                                   | UN 1307   |
| ADR, IMDG, IATA:                       | UN 1307   |
| <b>14.2 UN proper shipping name</b>    |   |
| DOT:                                   | XYLENES   |
| ADR, IMDG, IATA:                       | XYLENES   |
| <b>14.3 Transport hazard class(es)</b> |   |
| DOT                                    |   |
| Class:                                 | 3   |
| Label:                                 |  |
| ADR, IMDG, IATA                        |   |
| Class:                                 | Class 3   |
| Label:                                 |  |
| <b>14.4 Packing group</b>              |   |
| DOT, ADR, IMDG, IATA:                  | PG II   |

# Safety Data Sheet

According to OSHA Hazard Communication 29 CFR Part 1910.1200

Version: 1.2

Revision: 4/26/2022

**Trade Name: CSS EMULSION™ - VINTAGE**

## SECTION 15 Regulatory information

### U.S. Federal Regulations:

#### CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

#### SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

| <u>Chemical Name</u> | <u>CAS-No.</u> |
|----------------------|----------------|
| Xylene               | 1330-20-7      |
| Ethylbenzene         | 100-41-4       |

#### TOXIC SUBSTANCES CONTROL ACT:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA components exist in this product.

### U.S. State Regulations:

#### NEW JERSEY RIGHT-TO-KNOW:

The following materials are non-hazardous, but are among the top five components in this product.

No NJ Right-To-Know components exist in this product.

#### PENNSYLVANIA RIGHT-TO-KNOW

The following non-hazardous ingredients are present in the product are at or greater than 3%.

No PA Right-To-Know components exist in this product.

#### CALIFORNIA PROPOSITION 65 CARCINOGENS

Warning: The following ingredients present in the product are known to the state of California to cause Cancer:

| <u>Chemical Name</u> | <u>CAS-No.</u> |
|----------------------|----------------|
| Ethylbenzene         | 100-41-4       |

#### CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS

Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

No Proposition 65 Reproductive Toxins exist in this product.

### International Regulations: As follows -

#### CANADIAN WHMIS:

This MSDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

**WHMIS Class:** No Information

# Safety Data Sheet

According to OSHA Hazard Communication 29 CFR Part 1910.1200

Version: 1.2

Revision: 4/26/2022

**Trade Name: CSS EMULSION™ - VINTAGE**

## SECTION 16 Other information

**Revision Date:** 12/1/2014 **Supersedes Date:** New SDS

**Datasheet produced by:** Elite Crete Systems

### HMIS Ratings:

|                |   |                      |   |                    |   |                             |   |
|----------------|---|----------------------|---|--------------------|---|-----------------------------|---|
| <b>Health:</b> | 2 | <b>Flammability:</b> | 3 | <b>Reactivity:</b> | 0 | <b>Personal Protection:</b> | X |
|----------------|---|----------------------|---|--------------------|---|-----------------------------|---|

**Volatile Organic Compounds, gr/ltr:** 400

DISCLAIMER: THE VOLATILE ORGANIC COMPOUND (VOC) CONTENT REPORTED HEREIN, IF ANY, IS BASED ON A MATERIAL VOC CALCULATION. NOTE THAT SEVERAL METHODS ARE USED FOR CALCULATING VOC CONTENT AND THAT STANDARDS/ REQUIREMENTS REGARDING VOC CONTENT VARY BY LOCATION/JURISDICTION. ACCORDINGLY, EMCO MAKES NO REPRESENTATIONS OR WARRANTIES, EXPRESS OR IMPLIED, REGARDING THIS MATERIAL'S COMPLIANCE WITH VOC STANDARDS/REQUIREMENTS APPLICABLE IN LOCATIONS/JURISDICTIONS WHERE THIS MATERIAL MAY BE SOLD OR USED.

### Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

|      |  |
|------|--|
| H225 | Highly flammable liquid and vapor.                                 |
| H226 | Flammable liquid and vapor.  |
| H315 | Causes skin irritation.  |
| H319 | Causes serious eye irritation.                                     |
| H332 | Harmful if inhaled.  |
| H335 | May cause respiratory irritation.                                  |
| H351 | Suspected of causing cancer.                                       |
| H373 | May cause damage to organs through prolonged or repeated exposure. |

### GHS PRECAUTIONARY STATEMENTS

|                |   |
|----------------|---|
| P201           | Obtain special instructions before use.   |
| P202           | Do not handle until all safety precautions have been read and understood.                           |
| P210           | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.      |
| P240           | Ground/bond container and receiving equipment.  |
| P241           | Use explosion-proof electrical/ventilating/lighting/equipment.                                      |
| P242           | Use only non-sparking tools.  |
| P243           | Take precautionary measures against static discharge.   |
| P260           | Do not breathe dust/fume/gas/mist/vapors/spray.   |
| P264           | Wash thoroughly after handling.   |
| P271           | Use only outdoors or in a well-ventilated area.   |
| P280           | Wear protective gloves/protective clothing/eye protection/face protection.                          |
| P301+P310      | IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician                                     |
| P302+P352      | IF ON SKIN: Wash with plenty of water   |
| P303+P361+P353 | IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. |
| P304+P340      | IF INHALED: Remove person to fresh air and keep comfortable for breathing.                          |



# Safety Data Sheet

According to OSHA Hazard Communication 29 CFR Part 1910.1200

Version: 1.2

Revision: 4/26/2022

## Trade Name: CSS EMULSION™ - VINTAGE

|                |  |
|----------------|--|
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P308+P313      | IF exposed or concerned: Get medical advice/attention.   |
| P312           | Call a POISON CENTER/doctor/physician if you feel unwell.  |
| P314           | Get medical advice/attention if you feel unwell.   |
| P321           | Specific treatment (see first aid section on this label).  |
| P331           | Do NOT induce vomiting.  |
| P332+P313      | If skin irritation occurs: Get medical advice/attention.   |
| P337+P313      | If eye irritation persists: Get medical advice/attention.  |
| P362+P364      | Take off contaminated clothing and wash it before reuse.   |
| P370+P378      | In case of fire: Use appropriate method to extinguish.   |
| P403+P233      | Store in a well-ventilated place. Keep container tightly closed.   |
| P403+P235      | Store in a well-ventilated place. Keep cool.   |
| P405           | Store locked up.   |
| P501           | Dispose of contents/container in accordance with local/regional/national/international regulations.                              |

### Icons for GHS Pictograms shown in Section 3 describing each ingredient:

|       |   |
|-------|---|
| GHS02 |   |
| GHS07 |  |
| GHS08 |  |

Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined, N.I. - No Information

The information on this SDS was obtained from sources which we believe to be reliable. However, the information provided is without any warranty, expressed or implied, regarding its correctness. Some information presented and conclusions drawn herein are from sources other than direct test data on the product itself. The information and recommendations are offered for the user's consideration and examination and should be used to make an independent determination of the methods to safeguard workers and the environment. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For these reasons we do not assume responsibility and expressly disclaim any liability for loss, damage, or expense arising out of or in any way connected with handling, storage, use, or disposal of this product. If the product is used as a component in another product, this SDS may not be applicable. It is the responsibility of the user to comply with all Federal, State, and Local laws and regulations.