According to OSHA Hazard Communication 29 CFR Part 1910.1200

Version: 1.1 Revision: 4/26/2022

Trade Name: SPARTIC-ALL™ RM - Clear Polyaspartic Coating - Part B

SECTION 1 Identification

Product Name: SPARTIC-ALL™ RM - Part B
Product Type: SPARTIC-ALL™ RM - Part B

Supplied by:

Elite Crete Systems 1151 Transport Drive Valparaiso, IN 46383 Toll Free: 888-323-4445 Tel: (219) 465-7671

elitecrete.com

For Emergency Medical Assistance:

Call Health & Safety Information Services

(1-866-303-6949)

For Emergency transportation Information:

CHEMTREC US DOMESTIC: 1-800-424-9300

CHEMTREC INTERNATIONAL: 1-703-527-3887

SECTION 2 Hazard(s) identification

*** EMERGENCY OVERVIEW ***: Flammable liquid and vapor. May cause allergic skin reaction.

GHS Classification

Eye Irrit.. 2, Flam. Liq. 3, STOT SE 3 RTI, Skin Irrit. 2

WHMIS-symbols:

D2B - Toxic material causing other toxic effects.



NFPA ratings (scale 0 - 4)



Health = 2 Fire = 3 Reactivity = 1

HMIS-ratings (scale 0 - 4)



Health 2
Fire = 2
Reactivity = 1

Personal Protection = X

2.1 Classification of the substance or mixture Classification according to regulation (EC) No 1272/2008

Symbol(s) of Product





Signal Word Warning

GHS HAZARD STATEMENTS

Flammable Liquid, category 3

H226

Flammable liquid and vapor.

Skin Irritation, category 1

H317

May cause allergic skin reaction.

Eye irritation, category 2

H319

Causes serious eye irritation.

According to OSHA Hazard Communication 29 CFR Part 1910.1200

Version: 1.1 Revision: 4/26/2022

Trade Name: SPARTIC-ALL™ RM - Clear Polyaspartic Coating - Part B

STOT, single exposure, category 3, RTI

H335 May cause respiratory irritation.

Aquatic Chronic, category 3

H412 Harmful to aquatic life with long lasting effects.

Classification according to Directive 67/548EEC or Directive 1999/45/EC

Xi: Sensitizing

R43 May cause sensitization by skin contact. R52/53 Harmful to aquatic life with long term effects.

GHS PRECAUTIONARY STATEMENTS

P210 Keep away from heat, hot surfaces, sparks, open flames and other

ignition sources. No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P280 Wear protective gloves/protective clothing/eye protection/face

protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water/shower.

P370+P378 In case of fire: Use appropriate method to extinguish.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with

local/regional/national/international regulations.

SECTION 3 Composition/information on ingredients

3.2 Mixture.

Description: Mixture of substances listed below with nonhazardous additives.

Non Hazardous/Hazardous components:

Identification #	Description	WT. %
CAS: 136210-30-5 EINECS: 429-270-1 Index Number:607-521- 00-8	Tetraethyl-N,N-(methylenedicyclohexane-4,1-diyl)bis-DL-asparate GHS Symbols: (67/548/EEC), EU R Phrases; (43/52,53), Classification: Xi R43-52/53, Aquatic Chronic 2, H412, Skin irrit. 2, skin H315, Sens. 1, H315/337.	< 65 75%
CAS: 98-56-6 EINECS: solvent Index Number;	Parachlorobenzotrifluoride GHS Symbols: GHS02,GHS07 Statements: H226,315,319,335	< 25-35%

Additional information: Balance of other ingredients are non-hazardous or less than 1% in concentration (or 0.1% for carcinogens, reproductive toxins, or respiratory sensitizers).

According to OSHA Hazard Communication 29 CFR Part 1910.1200

Version: 1.1 Revision: 4/26/2022

Trade Name: SPARTIC-ALL™ RM - Clear Polyaspartic Coating - Part B

SECTION 4 First aid measures



FIRST AID - EYE CONTACT: Immediately flush eyes with water. Flush eyes with water for a minimum of 15 minutes, occasionally lifting and lowering upper lids. Get medical attention promptly.

FIRST AID - SKIN CONTACT: Remove contaminated clothing. Wash skin with soap and water. Get medical attention. Wash clothing separately and clean shoes before reuse.

FIRST AID - INHALATION: Rescuers should put on appropriate protective gear. Remove from area of exposure. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Keep victim warm. Get immediate medical attention.

FIRST AID - INGESTION: DO NOT induce vomiting. Get medical attention immediately. Quickly give 3 or more glasses of water for the victim to drink.

Most Important symptoms and effects, both acute and delayed

Allergic reactions

Gastric or intestinal disorders

Dizziness

Coughing

Breathing difficulty

Hazards:

Condition may deteriorate with alcohol consumption.

Indication of any immediate medical attention and special treatment needed.

If swallowed, gastric irrigation with added, activated carbon.

Monitor circulation, possible shock treatment.

Medical supervision for at least 48 hours.

Treat Skin and mucous membrane with antihistamine and corticoid preparations.

SECTION 5 Firefighting measures

UNUSUAL FIRE AND EXPLOSION HAZARDS: Flammable liquid and vapor. Vapors/dust may cause flash fire or explosion. Vapors can travel to a source of ignition and flash back. Empty containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. Also, do not reuse container without commercial cleaning or reconditioning.

SPECIAL FIREFIGHTING PROCEDURES: As in any fire, wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear. Avoid use of solid water streams. Water runoff can cause environmental damage. Dike and collect water used to fight fire.

EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, Foam, Water Fog

SECTION 6 Accidental release measures

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASE OR SPILLED: Wear appropriate personal protective equipment. (See Exposure Controls / Personal Protection Section.) Eliminate all ignition sources. Evacuate unnecessary personnel. Prevent additional discharge of material if able to do so safely. Do not touch or walk through spilled material. Avoid runoff into storm sewers and ditches which lead to waterways. Ventilate spill area. Stay upwind of spill. Use only non-combustible material for clean-up. Use clean, non-sparking tools to collect absorbed materials. Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container.

According to OSHA Hazard Communication 29 CFR Part 1910.1200

Version: 1.1 Revision: 4/26/2022

Trade Name: SPARTIC-ALL™ RM - Clear Polyaspartic Coating - Part B

SECTION 7 Handling and storage





HANDLING: Use only in a well ventilated area. Avoid breathing vapor, fumes or mist. Avoid contact with eyes, skin, and clothing. Always open containers slowly to allow any excess pressure to vent. Follow all MSDS/label precautions even after containers are emptied because they may retain product residues.

STORAGE: Keep away from heat, sparks, and flame. Store containers in a cool, well ventilated place. Keep container closed when not in use.

SECTION 8 Exposure controls/personal protection

Ingredients with Occupational Exposure Limits

Chemical Name ACGIH TLV-TWA ACGIH-TLV STEL OSHA PEL-TWA OSHA PEL-CEILING

Parachlorobenzotrifluoride N.D. N.D. N.D. N.D. N.D.

Personal Protection



RESPIRATORY PROTECTION: NIOSH/MSHA approved respirators may be necessary if airborne concentrations are expected to exceed exposure limits.



SKIN PROTECTION: Wear impervious gloves to prevent contact with the skin. Wear protective gear as needed - apron, suit, boots.



EYE PROTECTION: Wear safety glasses with side shields (or goggles) and a face shield.



OTHER PROTECTIVE EQUIPMENT: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.



HYGENIC PRACTICES: Do not eat, drink, or smoke in areas where this material is used. Avoid breathing vapors. Remove contaminated clothing and wash before reuse. Wash thoroughly after handling. Wash hands before eating.

SECTION 9 Physical and chemical properties

Appearance: Liquid clear/amber **Physical State:** Liquid Odor: solvent **Odor Threshold:** N.D. Density, g/cm3: 1.14 (9.50 lbs/g.) pH: N.D. Freeze Point, °F: N.D. Viscosity: N.D. **Solubility in Water:** Insoluble **Explosive Limits, vol%:** 0.9 - 10.5Flash Point, °F: 276-282°F (136-139°C) 109°F (43°C) Boiling Range, °F:

Evaporation Rate: 0.9 (n-butyl acetate=1) Auto-ignition Temp., °F: N.D. Vapor Density: 6.2 (air=1) Vapor Pressure: N.D.

(See "Other information" Section for abbreviation legend)

According to OSHA Hazard Communication 29 CFR Part 1910.1200

Version: 1.1 Revision: 4/26/2022

Trade Name: SPARTIC-ALL™ RM - Clear Polyaspartic Coating - Part B

SECTION 10 Stability and reactivity

STABILITY: No Information

CONDITIONS TO AVOID: Avoid impact, friction, heat, sparks, flame and source of ignition. **INCOMPATIBILITY:** Prevent contact with strong oxidizing agents. Keep away from acids.

HAZARDOUS DECOMPOSITION PRODUCTS: No Information

HAZARDOUS POLYMERIZATION: No Information

SECTION 11 Toxicological information



Information on Toxicological Effects

EFFECTS OF OVEREXPOSURE - INHALATION: Breathing in the material may irritate the mucous membranes of the nose, throat bronchi and lungs. Vapors are irritating to the respiratory tract.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: Causes skin irritation. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

EFFECTS OF OVEREXPOSURE - EYE CONTACT: Causes eye irritation.

EFFECTS OF OVEREXPOSURE - INGESTION: Ingestion may cause gastrointestinal tract irritation.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: No Information

Primary Route(s) of Entry: Eye Contact, Ingestion, Inhalation, Skin Contact

Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Name according to EEC	Oral LD50, mg/kg	Dermal LD50, mg/kg	Vapor LC50, mg/L
	Parachlorobenzotrifluoride			
98-56-6		13,000	2,700	33

SECTION 12 Ecological information

ECOLOGICAL INFORMATION: No Information

SECTION 13 Disposal considerations



For more guidance and information contact our Waste Services Division at (262) 658-4000. Always dispose of any waste in accordance with all local, state, and federal regulations.

DISPOSAL METHOD: Dispose of waste in accordance with all local, state and federal regulations.

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASE OR SPILLED: Wear appropriate personal protective equipment. (See Exposure Controls / Personal Protection Section.) Eliminate all ignition sources. Evacuate unnecessary personnel. Prevent additional discharge of material if able to do so safely. Do not touch or walk through spilled material. Avoid runoff into storm sewers and ditches which lead to waterways. Ventilate spill area. Stay upwind of spill. Use only non-combustible material for clean-up. Use clean, non-sparking tools to collect absorbed materials. Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container.

According to OSHA Hazard Communication 29 CFR Part 1910.1200

Version: 1.1 Revision: 4/26/2022

Trade Name: SPARTIC-ALL™ RM - Clear Polyaspartic Coating - Part B

SECTION 14 Transport information

14.1 UN-Number

DOT:

ADR, IMDG, IATA: UN 2234

UN 2234

14.2 UN proper shipping

name

DOT: CHLOROBENZOTRITFLUORIDES

ADR, IMDG, IATA: UN2234 CHLOROBENZOTRITFLUORIDES

14.3 Transport hazard

class(es) DOT

Class 3

Label:

ADR, IMDG, IATA

Class 3

Label:

(M)

14.4 Packing group

DOT, ADR, IMDG, IATA: PG III

14.5 Environmental hazards:

Marine pollutant: This products ingredients are not classified by the DOT as a

Marine Pollutant (as defined by 49 CFR 172.101, Appendix B)

14.6 Special precautions for user

Danger code (Kemler):

No data available

No data available

14.7 Transport in bulk according to

Annex II of MARPOL73/78 and the No data available

IBC Code:

Transport/Additional information

ΔDR

Tunnel restriction code No data available

UN "Model Regulation": No data available

SECTION 15 Regulatory Information

According to OSHA Hazard Communication 29 CFR Part 1910.1200

Version: 1.1 Revision: 4/26/2022

Trade Name: SPARTIC-ALL™ RM - Clear Polyaspartic Coating - Part B

U.S. Federal Regulations:

CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Fire Hazard, Chronic Health Hazard

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

No Sara 313 components exist in this product.

TOXIC SUBSTANCES CONTROL ACT:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA components exist in this product.

U.S. State Regulations:

NEW JERSEY RIGHT-TO-KNOW:

The following materials are non-hazardous, but are among the top five components in this product.

Chemical NameCAS-No.No right to know components existN/A

PENNSYLVANIA RIGHT-TO-KNOW

The following non-hazardous ingredients are present in the product are at or greater than 3%.

Chemical NameCAS-No.No right to know components existN/A

CALIFORNIA PROPOSITION 65 CARCINOGENS

Warning: The following ingredients present in the product are known to the state of California to cause Cancer:

No Proposition 65 Carcinogens exist in this product.

CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS

Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

No Proposition 65 Reproductive Toxins exist in this product.

International Regulations: As follows -

CANADIAN WHMIS: No information

This MSDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

WHMIS Class: No Information

According to OSHA Hazard Communication 29 CFR Part 1910.1200

Version: 1.1 Revision: 4/26/2022

Trade Name: SPARTIC-ALL™ RM - Clear Polyaspartic Coating - Part B

SECTION 16 Other information

Revision Date: 1/7/2015 Supersedes Date: New SDS

Datasheet produced by: Elite Crete Systems

HMIS Ratings:

Health: 2	2 Flammability:	3	Reactivity:	1	Personal Protection:	Х
-----------	-----------------	---	-------------	---	----------------------	---

Volatile Organic Compounds, gr/ltr: 0

DISCLAIMER: THE VOLATILE ORGANIC COMPOUND (VOC) CONTENT REPORTED HEREIN, IF ANY, IS BASED ON A MATERIAL VOC CALCULATION. NOTE THAT SEVERAL METHODS ARE USED FOR CALCULATING VOC CONTENT AND THAT STANDARDS/ REQUIREMENTS REGARDING VOC CONTENT VARY BY LOCATION/JURISDICTION. ACCORDINGLY, EMCO MAKES NO REPRESENTATIONS OR WARRANTIES, EXPRESS OR IMPLIED, REGARDING THIS MATERIAL'S COMPLIANCE WITH VOC STANDARDS/REQUIREMENTS APPLICABLE IN LOCATIONS/JURISDICTIONS WHERE THIS MATERIAL MAY BE SOLD OR USED.

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

GHS HAZARD STATEMENTS

Flammable Liquid, category 3	H226+H225 Flammable liquid and vapor. Highly flammable		
Skin Irritation, category 1		liquid/vapor	
Eye irritation, category 2	H317	May cause allergic skin reaction.	
STOT, single exposure, category 3, RTI	H319	Causes serious eye irritation.	
Aquatic Chronic, category 3	H335	May cause respiratory irritation.	
	H412	Harmful to aquatic life with long lasting effects.	

Classification according to Directive 67/548EEC or Directive 1999/45/EC

67/548EEC or Directive 1999/45/

Xi: Sensitizing

R43 May cause sensitization by skin contact.

R52/53 Harmful to aquatic life with long term effects.

GHS PRECAUTIONARY STATEMENTS

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P370+P378	In case of fire: Use appropriate method to extinguish.
P403+P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

According to OSHA Hazard Communication 29 CFR Part 1910.1200

Version: 1.1 Revision: 4/26/2022

Trade Name: SPARTIC-ALL™ RM - Clear Polyaspartic Coating - Part B

Icons for GHS Pictograms shown in Section 3 describing each ingredient:

GHS02



Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined, N.I. - No Information

The information on this SDS was obtained from sources which we believe to be reliable. However, the information provided is without any warranty, expressed or implied, regarding its correctness. Some information presented and conclusions drawn herein are from sources other than direct test data on the product itself. The information and recommendations are offered for the user's consideration and examination and should be used to make an independent determination of the methods to safeguard workers and the environment. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For these reasons we do not assume responsibility and expressly disclaim any liability for loss, damage, or expense arising out of or in any way connected with handling, storage, use, or disposal of this product. If the product is used as a component in another product, this SDS may not be applicable. It is the responsibility of the user to comply with all Federal, State, and Local laws and regulations.