According to 1907/2006/EC (REACH) and 1272/2008/EC (CLP)

#### Version: 1.4

1

Revision: 11/7/2023

## Trade Name: HERMETIC<sup>™</sup> 4.8S Urethane – Thermal Shock Resistant Slurry - Part C

## Identification of the substance/mixture and of the company/undertaking

- 1.1 Product identifier Trade Name: HERMETIC <sup>™</sup> 4.8S Urethane - Part C
- 1.2 Article No.: HERMETIC<sup>™</sup> 4.8S Urethane Part C

#### 1.3 Details of the supplier of the Safety Data Sheet Manufacturer:

Elite Crete Systems 1151 Transport Drive Valparaiso, IN 46383 Toll Free: 888.323.4445 Tel: (219) 465-7671 elitecrete.com

#### **1.4 Emergency telephone number:**

CHEMTREC US DOMESTIC: (800-424-9300) CHEMTREC INTERNATIONAL: (703-527-3887)

## 2 Hazards identification

## 2.1 Classification of the substance or mixture

#### GHS Classification in accordance with CFR 1910 (OSHA HCS)

The product is not classified as hazardous according to EU parliament and councils directive 1999/45/EF.

#### 2.2 Label elements

#### Labeling according to Regulation (EC) No 1272/2008:

Contains: Portland Cement

Hazard pictograms:



GHS05

P264

GHS07

## Signal Word: Danger

## Hazard Statements:

H315	Causes skin irritation.
H317	May cause allergic skin reaction.
H318	May cause respiratory irritation.

#### **Precautionary Statements:**

P102	Keep out of reach of children.
P280	Wear protective gloves/protective clothing/eye protection/face protection
P261	Avoid breathing dust.
P302+352	IF ON SKIN: wash with plenty of soap and water.
P305 +351+338.	IF IN EYES: rinse cautiously with water for several minutes. Remove contact lenses, If present and easy to do so. Continue rinsing.
P402 +404	Store in a dry place. Store in a closed container.
P501	Dispose of contents/container in accordance with local regulations.
•••	precautionary Statements:
D271 LLCO	only outdoors or in well ventilated area

Wash contaminated skin thoroughly after handling.

## According to 1907/2006/EC (REACH) and 1272/2008/EC (CLP)

## Version: 1.4

## Revision: 11/7/2023

## Trade Name: HERMETIC™ 4.8S Urethane – Thermal Shock Resistant Slurry - Part C

P304+340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P333+313 If skin irritation or rash OCCURS: get medical advice/Attention.

P361 Remove/take off immediately all contaminated clothing.

P362 Take off contaminated clothing before reuse.

P403+233 Store in well-ventilated place. Keep container tightly closed.

## 2.3. Other hazards

The grain size distribution of silica sand means that it is not hazardous. However, any respirable Crystalline Silica dust generated by processing and handling of silica sand may cause health effects. (EH40 Long term Exposure limit for Silica. Respirable crystalline is 0. 3mg.m3

## 3 Composition/information on ingredients

## 3.2 Mixture.

Description: Mixture of substances listed below with nonhazardous additives.

## Hazardous components:

Identification #	Description	WT. %
CAS: 65997-15-1 EC No: 266-043-4 Index No:	Portland cement Classification (EC1272/2008) Classification (67/54)   Skin Irrit. 2-H315 Xi: R41, R37/38. R4   Eye Dam. 1-H318 Skin Sens. 1-H317   STOT SE 3-H335 State 1	
CAS: 14808-60-7 EC No: 238-878-4 Index: No:	ALPHA QUARTZ Classification (EC1272/2008) Classification (67/548/EEC) Not Classified Not Classified	70%-82%
CAS: 1305-62-0	CALCIUM HYDROXIDE SLAKE LIME HYDRATED LIME Classification (EC1272/2008) Not Classified Classified	) 1-6%

Additional information: Balance of other ingredients are non-hazardous or less than 1% in concentration (or 0.1% for carcinogens, reproductive toxins, or respiratory sensitizers). Additional H statements see Sec 16.

## 4 First aid measures

## 4.1 Description of first aid measures

## After inhalation:

If breathing becomes difficult, remove victim to fresh air. If necessary, use artificial respiration to support vital functions. Seek medical attention if breathing difficulty continues. DO NOT INDUCE VOMITING

## After skin contact:

Wash skin thoroughly after handling. Seek medical attention if irritation develops and persists. Remove contaminated clothing. Launder contaminated clothing before re-use.

## After eye contact:

If product enters the eyes, open eyes while under gentle running water for at least 15 minutes. Seek medical attention.

## After eye contact:

If product enters the eyes, open eyes while under gentle running water for at least 15 minutes. Seek medical attention.

According to 1907/2006/EC (REACH) and 1272/2008/EC (CLP)

#### Version: 1.4

Revision: 11/7/2023

## Trade Name: HERMETIC<sup>™</sup> 4.8S Urethane – Thermal Shock Resistant Slurry - Part C

#### After swallowing:

If product is swallowed, call physician or poison control center for most current information. If professional advice is not available, do not induce vomiting. Never induce vomiting or give diluents Give large amounts of water or milk to a CONSCIOUS PERSON. <u>Never give (milk or water) to</u> <u>someone who is unconscious</u>, having convulsions, or who cannot swallow. Seek medical advice. Take a copy of the label and/or MSDS with the victim to the health professional.

### 4.2 Most important symptoms and effects, both acute and delayed.

**Acute**: This material may cause irritation to skin and eyes. Product may cause an allergic skin reaction. **Chronic:** Prolonged or repeated skin contact may cause skin reaction product can be removed with water wash exposed skin thoroughly. Seek medical attention if symptoms arise.

Target Organs: Acute: Eye, Skin Chronic: Skin

Hazards: Pre-existing skin or eye problems may be aggravated by exposure to this product.

4.3 Indication of any immediate medical attention and special treatment needed:

Treat symptoms and reduce over-exposure.

## **5** Firefighting measures

## 5.1 Extinguishing media

Suitable extinguishing agents: Use fire-extinguishing media appropriate for surrounding materials. 5.2 Special hazards arising from the substance or mixture: this product may form dust and can accumulate

- electrostatic charges, which may form electric discharges (ignition source). Use proper electrical grounding methods where airborne powder is removed mechanically.
- Hazardous decomposition products: Fire creates; Toxic gasses/vapors/fumes of: Carbon monoxide (CO), carbon dioxide (CO2)

## 5.3 Advice for Firefighters:

Use standard Protective equipment for firefighters appropriate for surrounding materials.

## 6 Accidental release measures

**6.1 Personal precautions, protective equipment and emergency procedures**: Personnel should be trained for spill response operations.

**6.2 Environmental precautions:** All work practices must be aimed at eliminating environmental contamination.

**6.3 Methods and material for containment and cleaning up:** Evacuate area. Contain spill if safe to do so. Prevent entry into drains, sewers, and other waterways. Soak up spilled material with an absorbent material and pick up and place in an appropriate waste container for disposal. Do not mix with other wastes. Dispose of in accordance with applicable Federal, State, and local procedures (see Section 13, Disposal Considerations).

## 7 Handling and storage

## 7.1 Precautions for safe handling

As with all chemicals, avoid getting this product ON YOU or IN YOU. Wash thoroughly after handling this product. Do not eat, drink, smoke, or apply cosmetics while handling this product. Avoid breathing dust/vapors generated by this product. **Use in a well-ventilated location or provide good ventilation before use**. Remove contaminated clothing immediately.

## 7.2 Conditions for safe storage, including any incompatibilities Storage:

#### Requirements to be met by storerooms and receptacles:

Provide good ventilation. and avoid contact with skin and eyes. Good general housekeeping procedure should be followed. Do not eat drink or smoke while using the material. Emergency showers should be readily available... Avoid contact with skin eyes. Do not inhale dust wear appropriate breathing equipment. Contact with eyes or skin may be irritating. Use only with good ventilation and PPE. Keep container closed when not in use.

### According to 1907/2006/EC (REACH) and 1272/2008/EC (CLP)

Version: 1.4

Revision: 11/7/2023

Trade Name: HERMETIC<sup>™</sup> 4.8S Urethane – Thermal Shock Resistant Slurry - Part C

7.3 Specific end use(s): use within the time period as recommended on the technical data sheet.

## 8 Exposure controls/personal protection

#### Additional information about design of technical facilities:

Use with adequate ventilation to ensure exposure levels are maintained below the limits provided above. Use local exhaust ventilation to control airborne dust. Ensure eyewash/safety shower stations are available near areas where this product is used.

#### 8.1 Control parameters

#### Ingredients with limit values that require monitoring at the workplace:

Currently, International exposure limits are not established for the components of this product. Please check with competent authority in each country for the most recent limits in place.

### 8.2 Exposure controls

#### Personal protective equipment:

#### General protective and hygienic measures:

The following information on appropriate Personal Protective Equipment is provided to assist employers in complying with OSHA regulations found in 29 CFR Subpart I (beginning at 1910.132) or equivalent standard of Canada, or standards of EU member states (including EN 149 for respiratory PPE, and EN 166 for face/eye protection), and those of Japan. Please reference applicable regulations and standards for relevant details.

**Respiratory protection:** Maintain airborne contaminant concentrations below guidelines listed above, if applicable. If necessary, use only respiratory protection authorized in the U.S. Federal OSHA Respiratory Protection Standard (29 CFR 1910.134), equivalent U.S. State standards, Canadian CSA Standard Z94.4-93, the European Standard EN149, or EU member states.

**Protection of hands:** Use chemical resistant gloves to prevent skin contact. If necessary, refer to U.S. OSHA 29 CFR 1910.138 or appropriate Standards of Canada.

Protective gloves

#### Material of gloves:

The selection of suitable gloves does not only depend on the material, but also on the quality, and varies from manufacturer to manufacture. Nitrile gloves are a good choice for using this product.

#### Penetration time of glove material:

The exact break through time has to be determined by the manufacturer of the protective gloves. DO NOT exceed the breakthrough time set by the Manufacturer.

**Eye protection:** Safety glasses or chemical goggles as appropriate to prevent eye contact. If necessary, refer to U.S. OSHA 29 CFR 1910.133 or appropriate Canadian Standards.

According to 1907/2006/EC (REACH) and 1272/2008/EC (CLP)

### Version: 1.4

Revision: 11/7/2023

## Trade Name: HERMETIC<sup>™</sup> 4.8S Urethane – Thermal Shock Resistant Slurry - Part C

Tightly sealed goggles

### **Body Protection:**

Use body protection appropriate to prevent contact (e.g. lab coat, overalls). If necessary, refer to appropriate Standards of Canada, or appropriate Standards of the EU, Australian Standards, or relevant Japanese Standards.

Exposure guidelines:

Revision: 11/7/2023

## Safety Data Sheet

According to 1907/2006/EC (REACH) and 1272/2008/EC (CLP)

de Name: HERMETIC™ 4.8S Uretha	ane – Thermal Shock Resistant Slurry - Part C
9 Physical and chemical properties	
9.1 Information on basic physical and chem	lical properties
General Information	
Appearance:	
Form:	Powder
Color:	White/gray
Odor:	N/A
Odor threshold:	N/A
pH-value:	9.0-9.6
Change in condition	N/A
Melting point/Melting range:	N/A
Boiling point/Boiling range:	
Flash point:	N/A
Flammability (solid, gaseous):	No data available
Auto/Self-ignition temperature:	N/A
Decomposition temperature:	No data available
Self-igniting:	No data available
Danger of explosion:	N/A
Explosion limits	
Lower + Upper:	Not established
Vapor pressure at:	Not established
Density at 20°C:	1.713 SG 14.27 LBS PER GALLON
Vapor pressure:	
Vapor density:	
Evaporation rate:	
Solubility in / Miscibility with Water:	Mixable
Specific Gravity 23 C: (Water = 1):	N/A
Viscosity:	
Dynamic:	No data available
Kinematic:	No data available
Solvent content:	No data available
Organic solvents:	No data available
VOC (EC) 9.2 Other information	0.0 g/l No data available

## 10 Stability and reactivity

Version: 1.4

10.1 Reactivity: no data available

**10.2 Chemical stability:** Product is stable under normal temperature conditions.

Thermal decomposition / conditions to be avoided: none known

10.3 Possibility of hazardous reactions: none known

10.4 Conditions to avoid: Avoid contact with strong oxidizers

**10.5 Incompatible materials:** Bases, Alkalis (inorganic), Acids, oxidizing polymers

10.6 Hazardous decomposition products: Fire or high temperatures create: carbon monoxide; carbon dioxide

According to 1907/2006/EC (REACH) and 1272/2008/EC (CLP)

Version: 1.4

Revision: 11/7/2023

# Trade Name: HERMETIC™ 4.8S Urethane – Thermal Shock Resistant Slurry - Part C

## 11 Toxicological information

### 11.1 Information on toxicological effects:

#### Inhalation

Irritating to respiratory system.

#### Ingestion

May cause discomfort if swallowed. May cause stomach pain or vomiting.

## Skin Contact

Irritating to skin. May cause sensitization by skin contact

#### Eye Contact

Risk of serious damage to eyes. Contact with concentrated chemical may very rapidly cause severe eye damage, possible loss of sight.

Medical considerations: Skin disorder and allergies.

## **12 Ecological information**

#### 12.1 Toxicity

- No data available
- 12.2 Persistence and degradability:
- Degradability 12.3 Bio accumulative potential:
  - N/A.
- 12.4 Mobility in soil: No data available
  - not relevant, due to form of product (powder)

## 12.5 Results of PBT and vPvB assessment

PBT.vPvB assessment not available, chemical assessment not required /not conducted

## **13 Disposal considerations**

#### 13.1 Waste treatment methods

#### **Recommendations:**

Waste disposal must be in accordance with appropriate Federal, State, and local regulations, those of Canada, Australia, EU Member States and Japan. Recommended to contact local licensed professional waste disposal service.

#### RCRA WASTE CODE: None Listed

EU WASTE CODE: Not Listed

## 14 Transport information

14.1 UN-Number	NO UN NUMBER REQUIRED NON-HAZARDOUS IN ALL
IMDG:	RESPECTS
ADR, DOT, IATA, TGD	NOT REGULATED, NOT DANGEROUS GOODS
14.2 UN proper shipping name	,
ADR, IMDG, IATA: DOT: TGD	NOT REGULATED, NOT DANGEROUS GOODS
14.3 Transport hazard class(es) DOT Class: Label:	NONE

According to 1907/2006/EC (REACH) and 1272/2008/EC (CLP)

Version: 1.4

Revision: 11/7/2023

	rethane – Thermal Shock Resistant Slurry - Part C
ADR, IMDG, IATA Class: Label:	NONE
IMDG	
Class: Label:	NONE
ΙΑΤΑ	
Class: Label:	NONE
14.4 Packing group DOT, ADR, IMDG, IATA:	NONE
14.5 Environmental hazards: Marine pollutant:	This products ingredients are not classified by the DOT as a Marine Pollutant (as defined by 49 CFR 172.101, Appendix B)
14.6 Special precautions for user	
Danger code (Kemler): EMS Number:	No data available No data available
14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:	No data available
Transport/Additional information	
ADR	
Tunnel restriction code	No data available
UN "Model Regulation":	No data available

## **15 Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture. United States (USA)

SARA: This product is not subject to the reporting requirements of Sections 302, 304 and 313 of Title III of the Superfund Amendments and Reauthorization Act.: None

Section 355 (extremely hazardous substances): None of the ingredients are listed.

Section 313 (Toxic Release Inventory): None of the ingredients are listed.

TSCA (Toxic Substances Control Act): All ingredients are listed.

#### Proposition 65 (California):

#### Chemicals known to cause cancer:

None of the ingredients is listed.

Canada

Canadian Domestic Substances List (DSL): All ingredients are listed

Canadian Ingredient Disclosure list (limit 0.1%): None of the ingredients are listed.

Canadian Ingredient Disclosure list (limit 1%): None of the ingredients are listed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

Safety Data Sheet According to 1907/2006/EC (REACH) and 1272/2008/EC (CLP)

Version: 1.4

Revision: 11/7/2023

	RMETIC™ 4.8S Urethane – Thermal Shock Resistant Slurry - Part
6 Other information	
Relevant phrase	s:
Acute Tox.	Acute Toxicity
Aquatic Acute.	Acute aquatic toxicity
H302: Harmfu	
H312: Harmfu	ul in contact with skin
	ul in contact with skin
	s skin irritation
Precautionary	
P102	Keep out of reach of children.
P280	Wear protective gloves/protective clothing/eye protection/face protection
P261	Avoid breathing dust.
P302+352	IF ON SKIN: wash with plenty of soap and water.
P305 +351+33	8. IF IN EYES: rinse cautiously with water for several minutes. Remove contact lens
	present and easy to do so. Continue rinsing.
P402 +404	Store in a dry place. Store in a closed container.
P501	Dispose of contents/container in accordance with local regulations.
P333+313 If s P361 Re P362 Ta	eathing. skin irritation or rash OCCURS: get medical advice/Attention. move/take off immediately all contaminated clothing. ke off contaminated clothing before reuse. ore in well-ventilated place. Keep container tightly closed.
R34: Causes b R43: May caus	n contact with skin urns. e sensitization by skin contact ul to aquatic organisms may cause long-term adverse effects in the aquatic environment.
IMDG: Internation DOT: US Departn IATA: Internationa ACGIH: American EINECS: Europea ELINCS: Europea CAS: Chemical A NFPA: National F HMIS: Hazardous	Agreement concerning the International Carriage of Dangerous Goods by Road nal Maritime Code for Dangerous Goods nent of Transportation. al Air Transport Association. In Conference of Governmental Industrial Hygienists. an Inventory of Existing Commercial Chemical Substances. an List of Notified Chemical Substances. bstracts Service (division of the American Chemical Society). ire Protection Association (USA). Materials Identification System (USA). centration, 50 percent.